



CoreLine Highbay Gen5

BY122P G5 LED300S/840 PSD NB

- Power supply unit with DALI interface - Beam angle 55° - 55°

CoreLine Highbay Gen5 delivers on the CoreLine promise of innovative, easy-to-use and high-quality luminaires. A reliable, highly-efficient luminaire with a very long-lifetime, it delivers great energy savings and requires less maintenance. At the same time, CoreLine Highbay is very easy to handle. The luminaire can be installed on your existing grid and the electrical connection is a straightforward task, with no need to open the luminaire and an external IP65 connector. With a choice of two beam angles: narrow and wide beam, you can adjust your lighting plan to suit your exact needs. This range also includes Interact Ready luminaires with integrated wireless communications and integrated movement and daylight sensors. So CoreLine Highbay Gen5 is ready to be used with any Interact connected lighting system.

Product data

General Information	
Light source color	840 neutral white
Light source replaceable	No
Number of gear units	2 units
Driver/power unit/transformer	Power supply unit with DALI interface
Driver included	Yes
Optic type	Beam angle 55°
Luminaire light beam spread	55°
Control interface	DALI
Connection	Connection unit 3-pole
Cable	Cable 0.3 m with connector 3-pole
Protection class IEC	Safety class I
Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	For mounting on normally flammable surfaces
CE mark	Yes
ENEC mark	ENEC mark
Warranty period	5 years
Constant light output	No
Number of products on MCB of 16 A type B	6
Photobiological risk	Photobiological risk group 1 @200mm to EN62778

CoreLine Highbay Gen5

Photobiological risk specification	18.2 m
EU RoHS compliant	Yes
Unified glare rating CEN	22
Lighting Technology	LED
Brand	Philips

Light Technical

Luminous Flux	30,000 lumen
Saturated Red (R9)	<50
Luminous Efficacy (rated) (Nom)	146 lm/W
Color rendering index (CRI)	>80
Flickering value (PstLM)	0.5
Stroboscopic effect value (SVM)	1

Operating and Electrical

Input Voltage	220 to 240 V
Line Frequency	50 or 60 Hz
Input Frequency	50 or 60 Hz
Power Consumption	205 W
Inrush current	60 A
Inrush time	600 ms
Power Factor (Fraction)	0.95

Temperature

Ambient temperature range	-30 to +50 °C
---------------------------	---------------

Controls and Dimming

Dimmable	Yes
----------	-----

Mechanical and Housing

Housing Material	Aluminum die-cast
Reflector material	-
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Fixation material	-
Housing Color	Dark gray
Optical cover/lens finish	Clear
Overall height	126 mm
Overall diameter	393 mm

Approval and Application

Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
-------------------------	--

Mech. impact protection code	IK08 [5 J vandal-protected]
Sustainability rating	-

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Init. Corr. Color Temperature	4000 K
Initial chromaticity	(0.385, 0.380) SDCM<5
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)


Control gear failure rate at median useful life 50000 h	5 %
Control gear failure rate at median useful life 100000 h	10 %
Lumen maintenance at median useful life* 50000 h	L85
Lumen maintenance at median useful life* 100000 h	L65

Application Conditions

Performance ambient temperature Tq	35 °C
Maximum dim level	13%
Suitable for random switching	Yes

Product Data

Full product code	871951495602500
Order product name	BY122P G5 LED300S/840 PSD NB
EAN/UPC - Product	8719514956025
Order code	911401632808
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material number (12NC)	911401632808
Net weight	6.290 kg
Full product name	BY122P G5 LED300S/840 PSD NB
EAN/UPC - Case	8719514956025



CoreLine Highbay Gen5

Dimensional drawing

