


Lodi Slim Downlight



- Economic circular LED performance downlight suitable for semi-commercial and residential applications
- Low profile design with integral driver
- Ideal for use in areas with shallow ceiling voids
- Supplied pre-wired with 300mm of cable



INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	SDCM	BEAM ANGLE	CLASS	IP
220 - 240V	50Hz	-15°C to 25°C	L70 25,000	Ra 80	6	115°	2	IP20

CODE	DESCRIPTION	WATTAGE	CCT	LUMENS	LM/W	UGR	A	B	TRADE
ALODLED/150/CW		16W		1730lm	108lm		170mm	150mm	£14.65
ALODLED/200/CW	Cool White	20W	4000K	2180lm	109lm	30	220mm	175mm	£20.65
ALODLED/250/CW		24W		2640lm	110lm	29	280mm	200mm	£30.35
ALODLED/150/WW		16W		1640lm	103lm		165mm	150mm	£14.65
ALODLED/200/WW	Warm White	20W	3000K	2090lm	105lm	30	190mm	175mm	£20.65
ALODLED/250/WW		24W		2520lm	105lm	29	215mm	200mm	£30.35

*UGR Value based on (4H - 8H)

CODE (ACCESSORIES)	DESCRIPTION	TRADE
ASLED/3NM	1.5W Non-Maintained	£49.55

