

PRODUCT-DETAILS

F202 F-25/0.03

F202 F-25/0.03 Residual Current Circuit Breaker 2P F type 30 mA



Algemene informatie

Type	F202 F-25/0.03
Artikelnummer	2CSF202325R1250
EAN	8012542992738
Omschrijving	F202 F-25/0.03 Residual Current Circuit Breaker 2P F type 30 mA
Omschrijving	The RCCBs F200 series assures protection to people and installations against fault current to earth. Type F offers the same range of protection and functionality as an RCCB Type A APR, this means that they detect sinusoidal AC currents as well as pulsating DC currents.

Circular Value

Circular Design Principles Recyclability Rate	Design for Closing Resource Loops - Standard EN45555 - 52,5 %
Sustainable Material Content	0 %
End of Life Instructions	9AKK108468A4361

Eco Transparency

Milieuproductverklaring - EPD	9AKK108467A3700
----------------------------------	-----------------

Technical

Normen	IEC/EN 61008 IEC/EN 62423
Type reststroom	F type
Toegekende spanning (U_r)	230 V
Nominaal bedrijfsvoltage	230 V
Nominaal isolatievoltage (U_i)	500 V
Nominale impuls grensvoltage (U_{imp})	4 kV
Ingangsspanningstype	AC
Toegekende stroom (I_n)	25 A
Nominale resterende stroom	30 mA
Nominale voorwaardelijke kortsluitstroom (I_{nc})	10 kA
Nominaal vermogen kortsluitvermogen (I_{cs})	1 kA
Stootspanningsvastheid	4 kA
Toegekende frequentie (f)	50 ... 60 Hz
Vermogensverlies	at Rated Operating Conditions per Pole 1 W
Aansluiting voeding	Arbitrary
Elektrisch uithoudingsvermogen	10000 cycle
Aantal polen	2
Bedieningskenmerk	Instantaneous (APR High Immunity)
Montagetype	DIN-Rail
Opties	None
Accessoires beschikbaar	Yes
Verbindingscapaciteit	Busbar 10 mm ² Rigid 25 ... 25 mm ² Flexible 25 ... 25 mm ²
Nominale doorsnede	4 - Meerdradig 0...25 mm ² 1 - Vaste kern 25...25 mm ²

Environmental

Omgevingstemperatuur	-25...55 °C
Omgevingsluchttemperatuur	Werking -25...55 °C
Beschermingsgraad	IP2X
Verontreinigingsgraad	2
Weerstand tegen trillingen volgens IEC 60068-2-6	0.1 mm or 1 g - 20 cycles at 5...150...5 Hz
Schokweerstand volgens IEC 60068-2-27	25g 2 shocks 13 ms
RoHS-status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS-informatie	9AKK106713A5612
REACH-verklaring	9AKK108467A9482
Milieu-informatie	Refer to RoHS
SCIP	18f132b0-8f03-4611-9c59-dba03cc369bf Italy (IT)
Rapport over conflictmineralen (CMRT)	9AKK108468A3363

Technical UL/CSA

Kortsluitstroomwaarde (SCCR)	30 mA
------------------------------	-------

Dimensions

Breedte in module-eenheden	2
Product netto breedte	0.035 m
Product netto hoogte	0.085 m
Product netto diepte	0.069 m
Product netto gewicht	0.200 kg
Inbouwdiepte (t ₂)	69 mm

Ordering

Minimale bestelhoeveelheid	1 stuk
Pakketniveau 1 Units	doos 1 stuk
Pakketniveau 1 Brutogewicht	0.235 kg

Certificates and Declarations

Conformiteitsverklaring - CE	9AKK106713A5612
------------------------------	-----------------

Installation

Instructies en handleidingen	9AKK107991A6127
------------------------------	-----------------

Popular Downloads

Gegevensblad, technische informatie	9AKK107991A8329
-------------------------------------	-----------------

Classifications

ETIM 8	EC000003 - Aardlekschakelaar
ETIM 9	EC000003 - Aardlekschakelaar
WEEE-categorie	5. Small Equipment (No External Dimension More Than 50 cm)
AEEA B2C / B2B	Business To Consumer
CN8	85363030
eClass	V11.0 : 27142201
Object classificatiecode	F

Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
2CDS200912R0001	S2C-H6R Auxiliary Contact	S2C-H6R	2	piece
2CDS200922R0001	S2C-S/H6R Signal / Auxiliary Contact	S2C-S/H6R	2	piece
2CDS200946R0001	S2C-H6-11R Auxiliary Contact	S2C-H6-11R	1	piece
2CDS200946R0003	S2C-H6-02R Auxiliary Contact	S2C-H6-02R	1	piece
2CDS200946R0002	S2C-H6-20R Auxiliary Contact	S2C-H6-20R	1	piece
2CSS200933R0011	F2C-A1 Shunt trip	F2C-A1	1	piece
2CSS200933R0012	F2C-A2 Shunt trip	F2C-A2	1	piece
2CSS200911R0005	S2C-UA 230 AC Undervoltage release	S2C-UA 230 AC	1	piece
2CSS200911R0007	S2C-UA 24 DC Undervoltage release	S2C-UA 24 DC	1	piece
2CSS200911R0002	S2C-UA 24 AC Undervoltage release	S2C-UA 24 AC	1	piece
2CSS200911R0008	S2C-UA 48 DC Undervoltage release	S2C-UA 48 DC	1	piece
2CSS200911R0004	S2C-UA 110 AC Undervoltage release	S2C-UA 110 AC	1	piece
2CSS200911R0006	S2C-UA 400 AC Undervoltage release	S2C-UA 400 AC	1	piece
2CSS200911R0001	S2C-UA 12 DC Undervoltage release	S2C-UA 12 DC	1	piece
2CSS200911R0010	S2C-UA 230 DC Undervoltage release	S2C-UA 230 DC	1	piece
2CSS200911R0009	S2C-UA 110 DC Undervoltage release	S2C-UA 110 DC	1	piece
2CSS200911R0003	S2C-UA 48 AC Undervoltage release	S2C-UA 48 AC	1	piece
2CSS200910R0005	S2C-OVP1 Overvoltage release	S2C-OVP1	1	piece
2CSS200993R0005	S2C-OVP2 Overvoltage release	S2C-OVP2	1	piece
2CSF200997R0013	F2C-CM Motor operating device	F2C-CM	1	piece
2CSF200996R0013	F2C-ARI Auto-reclosing unit	F2C-ARI	1	piece
2CSF200995R0013	F2C-ARI30 Auto-reclosing unit	F2C-ARI30	1	piece
2CSF200992R0005	F2C-ARH Auto-reclosing unit	F2C-ARH	1	piece
2CSF200991R0005	F2C-ARH -T Auto-reclosing unit with autotest	F2C-ARH -T	1	piece

Categorieën

Laagspanningsproducten en -systemen → Modulaire DIN rail producten → Aardlekschakelaars RCD's → Aardlekschakelaars RCD's

