



product description: double-sided self-adhesive tape  
 aggressive adhesive with high adhesion performance and high tack  
 performing at low temperatures  
 clear solvent acrylic adhesive  
 for most of surfaces

material: carrier - PE foam, liner - siliconised paper, adhesive - clear acrylic solvent  
 temperature resistance: -40 - +80 °C  
 width of tape: SP 15X1/10\_XX - 15 mm  
 SP 12X1/10\_XX - 12 mm  
 thickness of tape: 1 mm  
 length: 10 m  
 weight: SP 15X1/10\_XX - 0,045 kg/m  
 SP 12X1/10\_XX - 0,027 kg/m  
 storage: The product has a shelf life of 12 months when stored in original packaging at a temperature of 21 ° C with a relative humidity of 50%.

technical data:  
 (average values)

parameter	unit	value	testing method
<b>elongation</b>	%	219 ± 10%	AFERA 5004
<b>tensile strenght</b>	N/25 mm	23 ± 10%	AFERA 5004
<b>180° peel</b>	N/25 mm	14 ± 10%	AFERA 5001
<b>static shear</b>	h	2	AFERA 5012
<b>rolling ball tack</b>	cm	< 2	PSTC 6
<b>thickness liner</b>	µm	60 ± 10%	AFERA 5006