

PRODUCT-DETAILS

AF45-40-00 48-130V 50Hz / 48-130V 60Hz /
48-130V DC

AF45-40-00 48-130V 50Hz / 48-130V 60Hz / 48-
130V DC Contactor



General Information

| | |
|-----------------------|---|
| Extended Product Type | AF45-40-00 48-130V 50Hz / 48-130V 60Hz / 48-130V DC |
| Product ID | 1SBL337201R6900 |
| EAN | 3471522114495 |
| Catalog Description | AF45-40-00 48-130V 50Hz / 48-130V 60Hz / 48-130V DC Contactor |

| | |
|------------------|---|
| Long Description | <p>AF45 4-pole contactors are mainly used for controlling non-inductive or slightly inductive loads (i.e. resistance furnaces...) and generally for controlling power circuits up to 690 V AC and 440 V DC. The contactors can also be used for many other applications such lighting... The AF... contactors are fitted with an electronic coil interface which accepts a wide control voltage range, on AC 50/60 Hz or DC supplies. The same contactor can accept various supply voltages according to the different countries where the electrical equipment will be installed, or some fluctuation in the control voltage due to the local supply or network. The AF... contactors are also fully suitable for operation in AC or DC control circuit liable to voltage interruptions or voltage dip risks. Advantages: - Wide voltage range, e.g. 100 ... 250 V AC and DC - Can manage large voltage variations - Reduced power consumption - Very distinct closing and opening - Noise free - Can withstand voltage interruptions or voltage dips in the control supply (≤ 20 ms). The AF... series 4-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 4 N.O. main poles, front and side-mounted add-on auxiliary contact blocks - Control circuit: AC or DC operated - Accessories: a wide range of accessories is available.</p> |
|------------------|---|

Ordering

| | |
|------------------------|---------|
| Minimum Order Quantity | 1 piece |
|------------------------|---------|

| | |
|-----------------------|----------|
| Customs Tariff Number | 85364900 |
|-----------------------|----------|

Popular Downloads

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SNC001003C0202 |
| Instructions and Manuals | FPTC407734P0003 |
| CAD Dimensional Drawing | 2CDC001079B0201 |

Dimensions

| | |
|----------------------------|----------|
| Product Net Width | 92 mm |
| Product Net Depth / Length | 119.5 mm |
| Product Net Height | 110 mm |
| Product Net Weight | 1.42 kg |

Technical

| | |
|--|--|
| Number of Main Contacts NO | 4 |
| Number of Main Contacts NC | 0 |
| Number of Auxiliary Contacts NO | 0 |
| Number of Auxiliary Contacts NC | 0 |
| Standards | IEC/EN 60947-1, IEC/EN 60947-4-1, UL 508, CSA C22.2 No. 14, IEC 60077-1 (applicable parts), IEC 60077-2 (applicable parts), EN 50155 (applicable parts), TR CU 001/2011 (on request), IEC 61373, For compliance confirmation on applicable parts based on your application and combination, please consult your ABB sales representatives. |
| Rated Operational Voltage | Main Circuit 690 V |
| Rated Frequency (f) | Control Circuit 50 / 60 Hz Main Circuit 50 / 60 Hz |
| Conventional Free-air Thermal Current (I_{th}) | acc. to IEC 60947-4-1, Open Contactors $\Theta = 40\text{ }^{\circ}\text{C}$ 100 A |
| Rated Operational Current AC-1 (I_e) | (690 V) 40 $^{\circ}\text{C}$ 70 A (690 V) 55 $^{\circ}\text{C}$ 60 A (690 V) 70 $^{\circ}\text{C}$ 50 A |
| Rated Operational Current AC-3 (I_e) | (415 V) 55 $^{\circ}\text{C}$ 37 A (440 V) 55 $^{\circ}\text{C}$ 37 A (500 V) 55 $^{\circ}\text{C}$ 33 A (690 V) 55 $^{\circ}\text{C}$ 25 A (380 / 400 V) 55 $^{\circ}\text{C}$ 37 A (220 / 230 / 240 V) 55 $^{\circ}\text{C}$ 40 |
| Rated Operational Power AC-3 (P_e) | (415 V) 25 kW (440 V) 25 kW (500 V) 30 kW (690 V) 30 kW (380 / 400 V) 22 kW (220 / 230 / 240 V) 15 kW |
| Short-Circuit Protective | gG Type Fuses 80 A |

Devices

Rated Short-time at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 650 A
 Withstand Current Low at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 110 A
 Voltage (I_{cw}) at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 250 A
 at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 1000 A
 at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 370 A

Maximum Breaking Capacity $\cos \phi=0.45$ ($\cos \phi=0.35$ for $I_e > 100$ A) at 440 V 900 A
 $\cos \phi=0.45$ ($\cos \phi=0.35$ for $I_e > 100$ A) at 690 V 490 A

Maximum Electrical Switching Frequency (AC-1) 300 cycles per hour
 (AC-2 / AC-4) 150 cycles per hour
 (AC-3) 300 cycles per hour

Rated Operational Current DC-1 (I_e) (110 V) 2 Poles in Series, 40 °C 70 A
 (110 V) 2 Poles in Series, 55 °C 60 A
 (110 V) 2 Poles in Series, 70 °C 50 A
 (110 V) 3 Poles in Series, 40 °C 70 A
 (110 V) 3 Poles in Series, 55 °C 60 A
 (110 V) 3 Poles in Series, 70 °C 50 A
 (110 V) 4 Poles in Series, 40 °C 70 A
 (110 V) 4 Poles in Series, 55 °C 60 A
 (110 V) 4 Poles in Series, 70 °C 50 A
 (220 V) 3 Poles in Series, 40 °C 70 A
 (220 V) 3 Poles in Series, 55 °C 60 A
 (220 V) 3 Poles in Series, 70 °C 50 A
 (220 V) 4 Poles in Series, 40 °C 70 A
 (220 V) 4 Poles in Series, 55 °C 60 A
 (220 V) 4 Poles in Series, 70 °C 50 A
 (72 V) 1-Pole, 40 °C 70 A
 (72 V) 1-Pole, 55 °C 60 A
 (72 V) 1-Pole, 70 °C 50 A
 (72 V) 2 Poles in Series, 40 °C 70 A
 (72 V) 2 Poles in Series, 55 °C 60 A
 (72 V) 2 Poles in Series, 70 °C 50 A
 (72 V) 3 Poles in Series, 40 °C 70 A
 (72 V) 3 Poles in Series, 55 °C 60 A
 (72 V) 3 Poles in Series, 70 °C 50 A
 (72 V) 4 Poles in Series, 40 °C 70 A
 (72 V) 4 Poles in Series, 55 °C 60 A
 (72 V) 4 Poles in Series, 70 °C 50 A

Rated Operational Current DC-3 (I_e) (110 V) 2 Poles in Series, 40 °C 70 A
 (110 V) 2 Poles in Series, 55 °C 60 A
 (110 V) 2 Poles in Series, 70 °C 50 A
 (110 V) 3 Poles in Series, 40 °C 70 A
 (110 V) 3 Poles in Series, 55 °C 60 A
 (110 V) 3 Poles in Series, 70 °C 50 A
 (110 V) 4 Poles in Series, 40 °C 70 A
 (110 V) 4 Poles in Series, 55 °C 60 A
 (110 V) 4 Poles in Series, 70 °C 50 A
 (220 V) 3 Poles in Series, 40 °C 70 A
 (220 V) 3 Poles in Series, 55 °C 60 A
 (220 V) 3 Poles in Series, 70 °C 50 A
 (220 V) 4 Poles in Series, 40 °C 70 A
 (220 V) 4 Poles in Series, 55 °C 60 A
 (220 V) 4 Poles in Series, 70 °C 50 A
 (72 V) 1-Pole, 40 °C 70 A
 (72 V) 1-Pole, 55 °C 60 A
 (72 V) 1-Pole, 70 °C 50 A
 (72 V) 2 Poles in Series, 40 °C 70 A
 (72 V) 2 Poles in Series, 55 °C 60 A
 (72 V) 2 Poles in Series, 70 °C 50 A
 (72 V) 3 Poles in Series, 40 °C 70 A
 (72 V) 3 Poles in Series, 55 °C 60 A
 (72 V) 3 Poles in Series, 70 °C 50 A
 (72 V) 4 Poles in Series, 40 °C 70 A
 (72 V) 4 Poles in Series, 55 °C 60 A
 (72 V) 4 Poles in Series, 70 °C 50 A

Rated Operational Current DC-5 (I_e) (110 V) 2 Poles in Series, 40 °C 70 A
 (110 V) 2 Poles in Series, 55 °C 60 A

| | |
|---|--|
| | (110 V) 2 Poles in Series, 70 °C 50 A (110 V) 3 Poles in Series, 40 °C 70 A (110 V) 3 Poles in Series, 55 °C 60 A (110 V) 3 Poles in Series, 70 °C 50 A (110 V) 4 Poles in Series, 40 °C 70 A (110 V) 4 Poles in Series, 55 °C 60 A (110 V) 4 Poles in Series, 70 °C 50 A (220 V) 3 Poles in Series, 40 °C 50 A (220 V) 3 Poles in Series, 55 °C 50 A (220 V) 3 Poles in Series, 70 °C 50 A (220 V) 4 Poles in Series, 40 °C 70 A (220 V) 4 Poles in Series, 55 °C 60 A (220 V) 4 Poles in Series, 70 °C 50 A (72 V) 1-Pole, 40 °C 50 A (72 V) 1-Pole, 55 °C 50 A (72 V) 1-Pole, 70 °C 50 A (72 V) 2 Poles in Series, 40 °C 70 A (72 V) 2 Poles in Series, 55 °C 60 A (72 V) 2 Poles in Series, 70 °C 50 A (72 V) 3 Poles in Series, 40 °C 70 A (72 V) 3 Poles in Series, 55 °C 60 A (72 V) 3 Poles in Series, 70 °C 50 A (72 V) 4 Poles in Series, 40 °C 70 A (72 V) 4 Poles in Series, 55 °C 60 A (72 V) 4 Poles in Series, 70 °C 50 A |
| Rated Insulation Voltage (U _i) | acc. to IEC 60947-4-1 1000 V acc. to UL/CSA 600 V |
| Rated Impulse Withstand Voltage (U _{imp}) | 8 kV |
| Mechanical Durability | 10 million |
| Maximum Mechanical Switching Frequency | 300 cycles per hour |
| Rated Control Circuit Voltage (U _c) | 50 Hz 48 ... 130 V 60 Hz 48 ... 130 V DC Operation 48 ... 130 V |
| Coil Consumption | Holding at Max. Rated Control Circuit Voltage 50 Hz 7 V·A Holding at Max. Rated Control Circuit Voltage 50 Hz 2.8 W Holding at Max. Rated Control Circuit Voltage 60 Hz 7 V·A Holding at Max. Rated Control Circuit Voltage 60 Hz 2.8 W Pull-in at Max. Rated Control Circuit Voltage 50 Hz 210 V·A Pull-in at Max. Rated Control Circuit Voltage 60 Hz 210 V·A |
| Operate Time | Between Coil De-energization and NC Contact Closing 35 ... 115 ms Between Coil De-energization and NO Contact Opening 30 ... 110 ms Between Coil Energization and NO Contact Closing 30 ... 100 ms |
| Mounting on DIN Rail | TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH75-25 (75 x 25 mm Mounting Rail) acc. to IEC 60715 |
| Mounting by Screws (not supplied) | 2 x M6 screws placed diagonally |
| Connecting Capacity Main Circuit | Flexible with Cable End 6 ... 16 mm ² Rigid Cable 6 ... 25 mm ² |
| Connecting Capacity Auxiliary Circuit | Flexible with Cable End 0.75 ... 2.5 mm ² Rigid Cable 1 ... 4 mm ² |
| Degree of Protection | acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10 |
| Terminal Type | Screw Terminals |

Technical UL/CSA

| | |
|----------------------------------|--------------------|
| Maximum Operating Voltage UL/CSA | Main Circuit 600 V |
|----------------------------------|--------------------|

General Use Rating (600 V AC) 80 A
UL/CSA

Environmental

| | |
|---|--|
| Ambient Air Temperature | Close to Contactor for Storage -60 ... +80 °C Near Contactor for Operation in Free Air -40 ... 70 °C |
| Maximum Operating Altitude Permissible | Without Derating 3000 m |
| Shock and Vibration Withstand acc. to IEC 61373 | Category 1, Class B |
| Resistance to Shock acc. to IEC 60068-2-27 | Closed, Shock Direction: B1 10 g Open, Shock Direction: B1 5 g Shock Direction: A 20 g Shock Direction: B2 15 g Shock Direction: C1 20 g Shock Direction: C2 20 g |
| RoHS Status | Following EU Directive 2011/65/EU |

Certificates and Declarations

| | |
|----------------------------------|--------------------------|
| CB Certificate | CB_CN45489 |
| CCC Certificate | CCC_2018010304134049 |
| CQC Certificate | CQC2018010304134049 |
| CSA Certificate | CSA_1033838_LR056745 |
| Declaration of Conformity - CCC | 2020980304001624 |
| Declaration of Conformity - CE | 1SBD250803U1000 |
| Declaration of Conformity - UKCA | 1SBD250820U1000 |
| EAC Certificate | EAC_RU C-FR ME77 B01010 |
| GOST Certificate | GOST_POCCFRME77B07175 |
| UL Certificate | UL_20120830-E312527-10-1 |
| UL Listing Card | UL_E312527 |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Units | 1 piece |
| Package Level 1 Width | 142 mm |
| Package Level 1 Depth / Length | 190 mm |
| Package Level 1 Height | 136 mm |
| Package Level 1 Gross Weight | 1.42 kg |
| Package Level 1 EAN | 3471522114495 |
| Package Level 2 Units | box 8 piece |
| Package Level 2 Width | 503 mm |
| Package Level 2 Depth / Length | 153 mm |

| | |
|------------------------------|----------|
| Package Level 2 Height | 307 mm |
| Package Level 2 Gross Weight | 11.36 kg |
| Package Level 3 Units | 84 piece |

Classifications

| | |
|----------------------------|---|
| Object Classification Code | Q |
| ETIM 4 | EC000066 - Magnet contactor, AC-switching |
| ETIM 5 | EC000066 - Magnet contactor, AC-switching |
| ETIM 6 | EC000066 - Power contactor, AC switching |
| ETIM 7 | EC000066 - Power contactor, AC switching |
| ETIM 8 | EC000066 - Power contactor, AC switching |
| eClass | V11.0 : 27371003 |
| UNSPSC | 39121529 |

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

