

ALGINE NATYNK

SLI037031NW_PW



See
more

Downlight luminaire ALGINE NATYNK, with a power of 24 W, high light efficacy 110 lm/W. Lights up with neutral light - the most universal colour (4000K), which is suitable for the rooms we use on a daily basis, ensuring comfort during everyday activities. Designed for surface mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.

IK06



Power	24 W	Voltage	230 V
Luminous flux*	2650 lm (360°)	Colour temperature	4000 K
Colour of light	Neutral white	Beam angle	120 °
IK	6	Degree of protection (IP)	IP20


Technical data

Code	SLI037031NW_PW
Power	24 W
Nominal current	134 mA
Voltage	230 V
Energy consumption	24 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.7
Useful luminous flux*	2650 lm (360°)
Luminous flux**	1800 lm (360°)
Lamp efficacy	110 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/40 °
Lifespan	17000 h
Housing material	Plastic
IK	6
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	288x288x38 mm
For use	Inside
Assembly method	On the ceiling
Application	INT
Made in	PRC




Related documents



 User manual



 Declaration of Conformity



 Photometric file

