



CoreLine Wall-mounted

WL140V LED20S/830 PSU WH

- Power supply unit (ON/OFF) - Symmetrical - 120° x 120°

CoreLine wall-mounted solutions deliver on the CoreLine promise of innovative, easy-to-install and high quality luminaires. These circular-shaped, surface-mounted luminaires are suitable for both ceiling and wall installations and are easy to apply in circulation areas such as corridors, hallways and staircases. The modern, unobtrusive design, combined with a homogeneous light distribution, ensures this luminaire will blend into the architecture of most buildings. And thanks to the push-in connectors, installation of the CoreLine WL140V is fast and straightforward. This family includes Interact ready luminaires with integrated wireless communications, ready for use with Interact gateways, sensors and software.

Product data

General Information		Operating and Electrical	
Light source replaceable	Yes	Flickering value (PstLM)	1
Number of gear units	1 unit	Stroboscopic effect value (SVM)	1.6
Driver included	Yes	Beam angle of light source	120 degree(s)
Lighting Technology	LED	Light source color	830 warm white
Value ladder	Performance	Optic type	Symmetrical
Light Technical		Luminaire light beam spread	120° x 120°
Luminous Flux	2,100 lumen	Unified glare rating CEN	24
Saturated Red (R9)	<50	Operating and Electrical	
Correlated Color Temperature (Nom)	3000 K	Input Voltage	220-240 V
Luminous Efficacy (rated) (Nom)	105 lm/W	Line Frequency	50 or 60 Hz
Color rendering index (CRI)	>80	Input Frequency	50 or 60 Hz
		Initial CLO power consumption	- W

CoreLine Wall-mounted

Average CLO power consumption	- W
Power Consumption	20 W
Inrush current	14 A
Inrush time	0.007 ms
Power Factor (Fraction)	0.9
Connection	Push-in connector 6-pole
Cable	-
Number of products on MCB of 16 A type B	32

Temperature

Ambient temperature range	-20 to +40 °C
---------------------------	---------------

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit (ON/OFF)
Control interface	-
Constant light output	No

Mechanical and Housing

Housing Material	Polycarbonate
Reflector material	Polycarbonate
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Fixation material	-
Housing Color	White
Optical cover/lens finish	Opal
Overall height	85 mm
Overall diameter	390 mm

Approval and Application

Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK10 [20 J vandal-resistant]
Sustainability rating	-
Protection class IEC	Safety class II
Glow-wire test	Temperature 850 °C, duration 30 s
Flammability mark	-
CE mark	Yes
ENEC mark	ENEC mark
Warranty period	5 years

Photobiological risk	Photobiological risk group 0 @200mm to EN62778
Photobiological risk specification	0.2 m
EU RoHS compliant	Yes

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	(0.4338,0.4030) SDCM <3
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life	5 %
50000 h	
Lumen maintenance at median useful life*	-
35000 h	
Lumen maintenance at median useful life*	80
50000 h	
Lumen maintenance at median useful life*	-
75000 h	
Lumen maintenance at median useful life*	-
100000 h	

Application Conditions

Performance ambient temperature Tq	25 °C
Maximum dim level	Not applicable
Suitable for random switching	No

Product Data

Full product code	871951452873499
Order product name	WL140V LED20S/830 PSU WH
Order code	911401847582
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material number (12NC)	911401847582
Full product name	WL140V LED20S/830 PSU WH
EAN/UPC - Case	8719514528895



CoreLine Wall-mounted

Dimensional drawing

