



# **MASTER PL-L 4 Pin**

## MASTER PL-L 24W/830/4P 1CT/25

MASTER PL-L is a medium to high-wattage linear compact fluorescent lamp, typically used for general-illumination ceiling luminaires in retail, hospitality and office applications demanding higher lighting levels. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. It is designed for operation on electromagnetic as well as electronic HF control gear and is provided with a plug-in/pull-out lamp base.

#### **Warnings and Safety**

- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position as well as applied control gear
- $\boldsymbol{\cdot}$  Shorter lamp life when often switching and not well pre-heated electrodes
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

#### Product data

2G11 [2G11]
Sphere
330 [CCT of 3000K]
,800 lumen
Warm White (WW)
0.44
0.403
8000 K
75 lm/W
3

Color rendering index (CRI)	82
Operating and Electrical	
Power Consumption	24.2 W
Lamp Current (Nom)	0.345 A
Controls and Dimming	
Dimmable	Yes
Approval and Application	
Mercury (Hg) Content (Max)	2 mg
Mercury (Hg) Content (Nom)	2.0 mg


Datasheet, 2023, May 15 data subject to change

## **MASTER PL-L 4 Pin**

Energy Consumption kWh/1000 h	25 kWh
EPREL Registration Number	423,266
Product Data	
Full product code	871150070671340
Order product name	MASTER PL-L 24W/830/4P 1CT/25
Order code	927903208370

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	25
Material number (12NC)	927903208370
Full product name	MASTER PL-L 24W/830/4P 1CT/25
EAN/UPC - Case	8711500710796


### Dimensional drawing



 Product
 D (max)
 D1 (max)
 A (max)
 B (max)
 C (max)

 MASTER PL-L 24W/830/4P 1CT/25
 39.0 mm
 18.0 mm
 289.2 mm
 315 mm
 321.6 mm

#### Photometric data



Spectral Power Distribution Colour - MASTER PL-L 24W/830/4P 1CT/25



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.