

WLD+40004_DALI

WLD+40004_DALI



Power	6 W	Voltage	48 V
Colour temperature	3000 K	Colour of light	WW
Beam angle	24 °	Degree of protection (IP)	IP20

Technical data

Code	WLD+40004_DALI
Power	6 W
Nominal current	115 mA
Voltage	48 V
Energy consumption	6 kWh/1000h
Frequency	DC Hz
Protection class	III
Manufacturer of power supply	tuobo
Power factor	1
Useful luminous flux*	555 lm (360°)
Luminous flux**	370 lm (360°)
Lamp efficacy	93 lm/W
Luminous intensity	1050 cd
Colour temperature	3000 K
Colour of light	WW
Beam angle	24 °
RA	>90
Light source included	Yes
Producer of LED diodes	osram
Uniformity of color SDCM max	5
Dimmable	DALI
Working temperature range	-20 to +40 °
Lifespan	50000 h
Housing material	AL+PC
Degree of protection (IP)	IP20
Colour	Black
Dimension (AxBxC)	35x140x178 mm
For use	Inside
Assembly method	NA SZYŃE
Application	Inside
Made in	PRC
Other	DALI ,



Related documents



 Declaration of Conformity

<p>SYSTEM SHIFT CLICK & SHIFT</p>	<p>SYSTEM SHIFT CLICK & SHIFT</p>	
	<p>48V </p> <p>Luminaire assembly within the track on "click" and its free arrangement</p>	
<p>48V </p> <p>Montaż oprawy w obrobie szyby na „click” oraz możliwość swobodnego jej przesuwania</p>		