



TrueForce Core LED Industrial and Retail (Highbay – HPI/SON/HPL)

CorePro LED HPI MV 15Klm 105W840E40 100D

Philips TrueForce Core LED I&R lamps offer an easy and short payback LED solution to replace High Intensity Discharge (HID) lamps. The products bring the energy efficiency and long lifetime benefits of LED to HID replacement and provide instant saving and low initial investment. With the right lamp size and light distribution, you can easily retrofit TrueForce Core LED I&R lamps and bypass the existing ballast while enhancing the lighting quality.

Product data

Cap-Base E40 [E40]	
CE mark Yes	
EU RoHS compliant Yes	
Nominal lifetime 25,000 hour(s)	
Switching Cycle 50,000	
Lighting Technology LED	
Flux measurement reference Sphere	
Brand Philips	
Light Technical	
Color Code 840 [CCT of 4000K]	
Beam Angle (Nom) 100 degree(s)	

Luminous Flux	15,000 lumen		
Color Designation	Cool White (CW)		
Correlated Color Temperature (Nom)	4000 K		
Luminous Efficacy (rated) (Nom)	142 lm/W		
Color Consistency	<6		
Color rendering index (CRI)	80		
LLMF At End Of Nominal Lifetime (Nom) 70 %			
Operating and Electrical			
Line Frequency	50 to 60 Hz		
Input Frequency	50 to 60 Hz		
Power Consumption	105 W		
Wattage Equivalent	250 W		


Datasheet, 2023, May 5 data subject to change

TrueForce Core LED Industrial and Retail (Highbay - HPI/SON/HPL)

Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.9
Voltage (Nom)	110-240 V
Temperature	
Ambient temperature range	-20 °C to 45 °C
T-Case Maximum (Nom)	78 ℃
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Finish	Clear
Bulb Material	Plastic
Bulb Shape	T-shape
Approval and Application	
Energy Consumption kWh/1000 h	105 kWh


EPREL Registration Number	1,224,911
Product Data	
Full product code	871951442123300
Order product name	CorePro LED HPI MV 15Klm 105W840E40
	100D
Order code	929003161702
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material number (12NC)	929003161702
Net weight	1.130 kg
Full product name	CorePro LED HPI MV 15Klm 105W840E40
	100D
EAN/UPC - Case	8719514421240

Dimensional drawing




Product	D	С
CorePro LED HPI MV 15Klm 105W840E40 100D	162 mm	168 mm

Photometric data




Light Distribution Diagram - CorePro LED HPI MV 15Klm 105W840E40 100D



Spectral Power Distribution Colour - CorePro LED HPI MV 15Klm 105W840E40 100D


TrueForce Core LED Industrial and Retail (Highbay - HPI/SON/HPL)


Photometric data



Coloutus Presonantor 45 Philips Lighting BV. Page: 1

Lifetime





Life Expectancy Diagram - CorePro LED HPI MV 15Klm 105W840E40 100D

Lumen Maintenance Diagram - CorePro LED HPI MV 15Klm 105W840E40 100D



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.