


Empty enclosure

# TKS 3625-11-o



## TKS 3625-11-o

**Empty enclosure**

Productnumber: 14101201

Dimensions: 361 x 254 x 111 mm

Empty enclosure, protection class IP30, Polycarbonate, internal fixing points, for standard indoor installations, for mounting up to 26 WINSTA® plug connectors in conjunction with TKS AP adapter frames

**Box: Polycarbonate, grey, Lid: Polycarbonate, grey**



## Technical Data

### electrical characteristics

Rated operating voltage AC:	690 V
Rated operating voltage DC:	1000 V
Protection class:	II
Type of protection:	IP30
vented:	no
UL Type Rating:	not specified

### Colours

Base unit colour:	grey
Cover colour:	grey

### Dimensions

Width:	361 mm
Length:	254 mm
Height:	111 mm
Weight:	1.409 kg

### Material characteristics

UV-resistant:	yes
Halogen free:	yes
Flammability class according with UL94:	V2
Glow-wire flammability according to EN 60695-2-11:	960 °C

### mechanical properties

Type of fastening:	Wall/ceiling mounting
Impact strength:	IK07
Sealable:	yes
Cover screw torque:	1.2 Nm
Flange variant:	no

### mechanical properties

Type of top part:	Cover
Fastening:	internal fixing points

### Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-35 °C
Max. ambient temperature:	80 °C
24h ambient temperature:	60 °C
Installation location:	Indoors

### Sales Information

EAN:	4013902694372
Packing Unit Code:	C62
ETIM Class:	EC000261
Custom tariff number:	85389099

### Material

Base unit material:	Polycarbonate
Cover material:	Polycarbonate
Cover screw material:	Polyamide, glass-fibre reinforced

## Accessories

[19821601 - NS 35-216 - Standard rail](#)

[19400101 - TK ABL - External fixing lugs kit](#)

[89604101 - MABF 215-2 - Mast/pipe fixing set](#)

[19501201 - TK MPI-3625 - Mounting plate](#)

[19701201 - TK MPS-3625 - Mounting plate](#)

## Cable gland

