

Empty enclosure

ALS 1414-7



ALS 1414-7

Empty enclosure

Productnumber: 15100401

Dimensions: 139 x 139 x 73 mm

Empty enclosure, with protection class IP66, Aluminium, powder-coated painting, certified according to UL (UL 508 & CSA C22.2 No. 14-13, UL 50 & CSA 22.2 No. 94.1-7 & UL 50E & CSA C22.2 No. 94.2-7), for installations in the industrial arena and protected outside areas

Box: Aluminium, powder-coated painting, Lid: Aluminium, powder-coated painting, silver-grey, smooth sidewalls



Internal dimensions and mounting points correspond to the respective TK PS/PC dimension

Technical Data

electrical characteristics

Protection class:	I
Type of protection:	IP66
vented:	no
UL Type Rating:	4X, 12

Colours

Cover colour:	silver-grey
---------------	-------------

Dimensions

Width:	139 mm
Length:	139 mm
Height:	73 mm

Material characteristics

suitable for exterior use:	yes
Industry quality:	yes
Halogen free:	yes

mechanical properties

Type of fastening:	Wall/ceiling mounting
Impact strength:	IK09
Flange variant:	no
Stackable:	no
Type of top part:	Cover

Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-35 °C
Max. ambient temperature:	75 °C

Ambient conditions

24h ambient temperature:	60 °C
--------------------------	-------

Material

Base unit material:	Aluminium, powder-coated painting
Cover material:	Aluminium, powder-coated painting
Sealing material:	Silicone

Certificates

Test mark:	UL (UL 508 & CSA C22.2 No. 14-13, UL 50 & CSA 22.2 No. 94.1-7 & UL 50E & CSA C22.2 No. 94.2-7)
------------	--

Accessories

[15400601 - AL ALS-gro - External attachment set](#)

[19500401 - TK MPI-1111 - Mounting plate](#)

[19700401 - TK MPS-1111 - Mounting plate](#)

[19708001 - TS 15-80 - Standard rail](#)

[19709201 - TS 15-92 - Standard rail](#)

[19808101 - NS 35-81 - Standard rail](#)