

item number	H	A	thickness of metal sheet	weight kg/pc
BSKH 60 K_S	64	280	2	0,36
BSKH 60 K_F				0,41
BSKH 85 K_S	89	280	2	0,45
BSKH 85 K_F				0,53
BSKH 110 K_S	114	280	2	0,55
BSKH 110 K_F				0,64
BSKH 60 D_S	64	630	2	0,83
BSKH 60 D_F				0,96
BSKH 85 D_S	89	630	2	1,05
BSKH 85 D_F				1,22
BSKH 110 D_S	114	630	2	1,28
BSKH 110 D_F				1,48



product description: It is used for bending off of the cable ladder line or as a replacement of cable ladder adapting piece.

Couplings are a more cost-effective and versatile way of creating a tray branch in a horizontal direction.

Cut the side wall of the cable ladder to bend off c. 15 mm above the bottom – in the bottom perforation axis. It is necessary to use NCH.

To fix the connection use the bolt NSM 6X10. To protect the cables, the bolt head is inside the cable tray.

A bolt with a GMT surface finish is used for a tray with an F surface finish.

surface finish: S - Pre-Galvanized, zinc-layer 15 - 27 µm
F - Hot Dip Galvanized, zinc-layer 55 µm (min. 45 µm)

sales amount: á 1 pc

certification: EN 61537:02

storage: EN 60721-3-1

