

VIGA

SLI045003CW_PW

Linear luminaire VIGA, with a power of 18 W, high light efficacy 155 lm/W. It shines with a cold light colour (6000K), which is suitable for rooms where we need to be most focused and concentrated, such as technical workstations. Suitable for both surface and suspended mounting.

IK06



Power	18 W	Voltage	230 V
Luminous flux*	2800 lm (360°)	Colour temperature	6000 K
Colour of light	CW	Beam angle	120 °
IK	06	Degree of protection (IP)	IP20

Technical data


Code	SLI045003CW_PW
Power	18 W
Nominal current	130 mA
Voltage	230 V
Energy consumption	18 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.7
Useful luminous flux*	2800 lm (360°)
Luminous flux**	2300 lm (360°)
Lamp efficacy	155 lm/W
Colour temperature	6000 K
Colour of light	CW
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	PC
IK	06
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	76x600x26 mm
For use	Inside
Assembly method	On the ceiling, Suspended
Application	INT
Made in	PRC

Related documents



 User manual



 Declaration of Conformity



 Photometric file

