

Product Environmental Profile

iST 65r 3P+N



Schneider
Electric




General information

Representative product	iST 65r 3P+N - A9L916605
Description of the product	Protect electrical equipment against the direct or indirect effects of lightning or against transient overvoltage
Functional unit	Protect during 20 years against direct or indirect effects of lightning or against transient overvoltages electrical equipments connected to electrical networks with a rated operational voltage up to 1000 V AC or 1500 V DC



Constituent materials

Reference product mass 500 g including the product, its packaging and additional elements and accessories



Plastics	28.4%
Metals	24.7%
Others	46.9%



Substance assessment

Products of this range are designed in conformity with the requirements of the RoHS directive (European Directive 2011/65/EU of 8 June 2011) and do not contain, or only contain in the authorised proportions, lead, mercury, cadmium, hexavalent chromium or flame retardants (polybrominated biphenyls - PBB, polybrominated diphenyl ethers - PBDE) as mentioned in the Directive

As the products of the range are designed in accordance with the RoHS Directive (European Directive 2002/95/EC of 27 January 2003), they can be incorporated without any restriction in an assembly or an installation subject to this Directive.

Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website <http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page>



Additional environmental information

The iST 65r 3P+N presents the following relevant environmental aspects


Manufacturing	Manufactured at a Schneider Electric production site ISO14001 certified
Distribution	Weight and volume of the packaging optimized, based on the European Union's packaging directive Packaging weight is 54.1 g, consisting of cardboard (90.4%), paper (9.6%) Product distribution optimised by setting up local distribution centres
Installation	RefA9L916605 doesn't require any installation operations, the packaging waste is generated from installation phase.
Use	The product does not require special maintenance operations.
End of life	End of life optimized to decrease the amount of waste and allow recovery of the product components and materials This product contains electronic card (9.116g) that should be separated from the stream of waste so as to optimize end-of-life treatment. The location of these components and other recommendations are given in the End of Life Instruction document which is available on the Schneider-Electric Green Premium website http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page Recyclability potential: 26% Based on "ECO'DEEE recyclability and recoverability calculation method" (version V1, 20 Sep. 2008 presented to the French Agency for Environment and Energy Management: ADEME).



Environmental impacts

Reference life time	20 years			
Product category	Surge arresters and Surge protective devices type 1, 2 or 3 connected to low voltage power systems			
Installation elements	No special components needed			
Use scenario	Load factor : 100% of I _c Use rate: 100 % of the RLT			
Geographical representativeness	China			
Technological representativeness	Protect electrical equipment against the direct or indirect effects of lightning or against transient overvoltage			
Energy model used	Manufacturing	Installation	Use	End of life
	Energy model used: China	Electricity mix; AC; consumption mix, at consumer; 220V; CN	Electricity mix; AC; consumption mix, at consumer; 220V; CN	Electricity mix; AC; consumption mix, at consumer; 220V; CN

Compulsory indicators		iST 65r 3P+N - A9L916605						
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life	
Contribution to mineral resources depletion	kg Sb eq	7.13E-04	7.05E-04	0*	0*	7.82E-06	0*	
Contribution to the soil and water acidification	kg SO ₂ eq	1.94E+00	5.72E-03	2.95E-04	0*	1.93E+00	0*	
Contribution to water eutrophication	kg PO ₄ ³⁻ eq	5.12E-01	1.67E-03	6.78E-05	0*	5.10E-01	0*	
Contribution to global warming	kg CO ₂ eq	1.79E+03	3.69E+00	0*	0*	1.78E+03	0*	
Contribution to ozone layer depletion	kg CFC11 eq	1.47E-05	5.18E-07	0*	0*	1.42E-05	4.11E-09	
Contribution to photochemical oxidation	kg C ₂ H ₄ eq	2.29E-01	8.10E-04	0*	0*	2.28E-01	0*	
Resources use		Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Net use of freshwater	m ³	2.02E+00	3.42E-02	0*	0*	1.99E+00	0*	
Total Primary Energy	MJ	2.92E+04	4.91E+01	0*	0*	2.92E+04	0*	



Optional indicators		iST 65r 3P+N - A9L916605						
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life	
Contribution to fossil resources depletion	MJ	2.79E+04	3.86E+01	0*	0*	2.79E+04	0*	
Contribution to air pollution	m ³	1.86E+05	7.43E+02	0*	0*	1.85E+05	0*	
Contribution to water pollution	m ³	8.95E+04	8.46E+02	1.06E+01	0*	8.86E+04	0*	
Resources use		Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Use of secondary material	kg	8.39E-03	8.39E-03	0*	0*	0*	0*	
Total use of renewable primary energy resources	MJ	1.50E+03	1.98E+00	0*	0*	1.50E+03	0*	
Total use of non-renewable primary energy resources	MJ	2.77E+04	4.71E+01	0*	0*	2.77E+04	0*	
Use of renewable primary energy excluding renewable primary energy used as raw material	MJ	1.50E+03	8.77E-01	0*	0*	1.50E+03	0*	
Use of renewable primary energy resources used as raw material	MJ	1.10E+00	1.10E+00	0*	0*	0*	0*	
Use of non renewable primary energy excluding non renewable primary energy used as raw material	MJ	2.77E+04	4.32E+01	0*	0*	2.77E+04	0*	
Use of non renewable primary energy resources used as raw material	MJ	3.85E+00	3.85E+00	0*	0*	0*	0*	
Use of non renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*	
Use of renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*	
Waste categories		Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Hazardous waste disposed	kg	7.57E+01	1.75E+01	0*	0*	5.74E+01	7.94E-01	
Non hazardous waste disposed	kg	3.24E+02	1.13E+00	0*	0*	3.23E+02	0*	
Radioactive waste disposed	kg	1.15E-02	8.15E-04	1.63E-06	0*	1.06E-02	3.51E-06	
Other environmental information		Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Materials for recycling	kg	1.92E-01	2.39E-02	0*	0*	5.38E-02	1.14E-01	
Components for reuse	kg	0.00E+00	0*	0*	0*	0*	0*	
Materials for energy recovery	kg	1.66E-02	1.12E-03	0*	0*	0*	1.55E-02	
Exported Energy	MJ	0.00E+00	0*	0*	0*	0*	0*	

* represents less than 0.01% of the total life cycle of the reference flow

Life cycle assessment performed with EIME version EIME v5.7.0.3, database version 2016-11 in compliance with ISO14044.

The use phase is the life cycle phase which has the greatest impact on the majority of environmental indicators (based on compulsory indicators).

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

<i>Registration number</i>	ENVPEP1308014_V2-EN	<i>Drafting rules</i>	PCR-ed3-EN-2015 04 02
<i>Date of issue</i>	06/2018	<i>Supplemented by</i>	PSR-0005-ed2-EN-2016 03 29
<i>Validity period</i>	5 years	<i>Information and reference documents</i>	www.pep-ecopassport.org
<i>Independent verification of the declaration and data</i>			
Internal	X	External	
<i>The elements of the present PEP cannot be compared with elements from another program.</i>			
<i>Document in compliance with ISO 14021:2016 « Environmental labels and declarations - Self-declared environmental claims (Type II environmental labelling) »</i>			

Schneider Electric Industries SAS

Country Customer Care Center
<http://www.schneider-electric.com/contact>

35, rue Joseph Monier

CS 30323

F- 92506 Rueil Malmaison Cedex

RCS Nanterre 954 503 439

Capital social 896 313 776 €

www.schneider-electric.com

Published by Schneider Electric

ENVPEP1308014_V2-EN

© 2017 - Schneider Electric – All rights reserved

06/2018