

LED G4

WOJ+13842

LED source LED G4 2 W in silicone cover. It is perfect for use in households, hotels, shops, or restaurants as decorative or accent lighting, and can be installed in luminaires that have a G4 base. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Wide beam angle 270° ensures even illumination of the room.




Power	2 W	Voltage	12 V
Luminous flux**	165 lm (360°)	Colour temperature	3000 K
Colour of light	WW	Beam angle	270 °
Socket	G4		

Technical data

Code	WOJ+13842
Power	2 W
Nominal current	240 mA
Voltage	12 V
Energy efficiency class	G
Energy consumption	3 kWh/1000h
Frequency	0-50HZ Hz
Power factor	0,5
Useful luminous flux*	165 lm (360°)
Luminous flux**	165 lm (360°)
Lamp efficacy	82 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	270 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Socket	G4
Dimension (AxBxC)	13,5x36,5 mm
For use	Inside
Application	INT
Made in	PRC

Related documents



 Declaration of Conformity

