

Socket outlet combination

## STK 1414-K16



### STK 1414-K16

#### Socket outlet combination

Productnumber: 73010301

Dimensions: 315 x 450 x 195 mm

Socket outlet combination, protection class IP44, ready for connection in accordance with EN61439-3, with central terminal 4 - 25mm<sup>2</sup>, 5-pole, also suitable for feed-through looping of the supply cable, standard rails can be removed without tools for easy cable routing in the enclosure, CEE socket outlets with 20° inclination, easy combination with STK-Z additional enclosures or AK Air small distribution boards with flange openings (AK-F), incl. flanges

#### available modules: 14

#### equipped with:

- 4 x Miniature circuit breaker C 16 A, 1p
- 1 x Miniature circuit breaker C 16 A, 3p
- 1 x Residual Current Circuit Breaker (RCCB), 40/0.03A, 4-pole, type A
- 4 x SCHUKO® plug socket (on front), 230V
- 1 x CEE plug socket outlet (on front) 16A, 400V



## Technical Data

### Built-in devices

Residual Current Circuit Breaker (RCCB), 40/0.03A, 4-pole, type A:	1
Miniature circuit breaker C 16 A, 3p:	1
SCHUKO® plug socket (on front), 230V:	4
CEE plug socket outlet (on front) 16A, 400V:	1
Miniature circuit breaker C 16 A, 1p:	4

### electrical characteristics

Rated operating voltage AC:	400 V
Rated insulation voltage AC:	400 V
Protection class:	II
Type of protection:	IP44
vented:	yes
Number of N-potentials:	1
Number of rows:	1
Number of modules:	14
Number of modules per row:	14

### Colours

Base unit colour:	grey
Cover colour:	grey

### Dimensions

Width:	315 mm
Length:	450 mm
Height:	195 mm
Inner length:	430 mm
Inner width:	295 mm
Inner height:	106 mm
Weight:	5.7 kg

## Material characteristics

UV-resistant:	yes
Halogen free:	yes
Glow-wire flammability according to EN 60695-2-11:	850 °C

## mechanical properties

Type of fastening:	Wall mounting
Impact strength:	IK08
Sealable:	yes
Cover screw torque:	1.2 Nm
Flange variant:	yes

## Ambient conditions

max. relative humidity 25°C:	90 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25 °C
Max. ambient temperature:	40 °C
24h ambient temperature:	35 °C
Installation location:	protected outdoor areas

## Sales Information

EAN:	4013902689880
Packing Unit Code:	CT
ETIM Class:	EC000379
Custom tariff number:	85369095

## Material

Base unit material:	Polycarbonate, glass-fibre reinforced
Cover material:	Polycarbonate
Sealing material:	Polyurethane
Cover screw material:	Polyamide, glass-fibre reinforced
Hinged window material:	Polycarbonate

## Accessories

[73383001 - AK3 KS M50 - Combination cable gland](#)

[73383101 - AK3 KBL - Cable cover](#)

## Cable gland

