

Product Environmental Profile

SmartX Controller AS-P






General information

Representative product	SmartX Controller AS-P -SXWASPXXX10001
Description of the product	The SmartX Controller AS-P is a powerful device that can act as a standalone server and also control I/O modules and monitor and manage field bus devices. In a small installation, the embedded Automation Server acts as a stand-alone server, mounted with its I/O modules in a small footprint. In medium and large installations, functionality is distributed over multiple Automation Servers that communicate over TCP/IP.
Functional unit	Controller acts as server, control I/O modules and manage field bus devices during 10 years.



Constituent materials

Reference product mass	276 g including the product, its packaging and additional elements and accessories
-------------------------------	--



Substance assessment

Products of this range are designed in conformity with the requirements of the RoHS directive (European Directive 2011/65/EU of 8 June 2011) and do not contain, or only contain in the authorised proportions, lead, mercury, cadmium, hexavalent chromium or flame retardants (polybrominated biphenyls - PBB, polybrominated diphenyl ethers - PBDE) as mentioned in the Directive

As the products of the range are designed in accordance with above directive, they can be incorporated without any restriction in an assembly or an installation subject to this Directive.

Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website

http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium_page



Additional environmental information

The SmartX Controller AS-P presents the following relevant environmental aspects

Manufacturing	Manufactured at a Schneider Electric production site ISO14001 certified
Distribution	Weight and volume of the packaging optimized, based on the European Union's packaging directive Packaging weight is 33.3 g, consisting of cardboard (78%), paper (17%), LD-PE (5%) Product distribution optimised by setting up local distribution centres
Installation	Ref SXWASPXXX10001 does not require any installation operations.
Use	The product does not require special maintenance operations.
End of life	End of life optimized to decrease the amount of waste and allow recovery of the product components and materials This product contains electronic cards (130g) that should be separated from the stream of waste so as to optimize end-of-life treatment. The location of these components and other recommendations are given in the End of Life Instruction document which is available on the Schneider-Electric Green Premium website http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page Recyclability potential: 48% Based on Eco'DEEE method




Environmental impacts

Reference life time	10 years			
Product category	Active products			
Installation elements	No special components needed			
Use scenario	The product is in active mode 100% of the time with a power use of 3.3W nominal, for 10 years			
Geographical representativeness	Europe,			
Technological representativeness	The SmartX Controller AS-P is a powerful device that can act as a standalone server and also control I/O modules and monitor and manage field bus devices. In a small installation, the embedded Automation Server acts as a stand-alone server, mounted with its I/O modules in a small footprint. In medium and large installations, functionality is distributed over multiple Automation Servers that communicate over TCP/IP.			
Energy model used	Manufacturing	Installation	Use	End of life
	Energy model used: France	Electricity Mix; AC; consumption mix, at consumer; < 1kV; EU-27	Electricity Mix; AC; consumption mix, at consumer; < 1kV; EU-27	Electricity Mix; AC; consumption mix, at consumer; < 1kV; EU-27

Compulsory indicators		SmartX Controller AS-P - SXWASPXXX10001					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to mineral resources depletion	kg Sb eq	2.43E-03	2.43E-03	0*	0*	7.78E-06	0*
Contribution to the soil and water acidification	kg SO ₂ eq	1.30E+00	1.27E-02	1.63E-04	0*	1.29E+00	0*
Contribution to water eutrophication	kg PO ₄ ³⁻ eq	5.19E-02	3.46E-03	3.74E-05	0*	4.84E-02	5.29E-05
Contribution to global warming	kg CO ₂ eq	1.79E+02	8.60E+00	3.56E-02	0*	1.71E+02	1.54E-01
Contribution to ozone layer depletion	kg CFC11 eq	4.25E-05	1.07E-06	0*	0*	4.15E-05	7.23E-09

Contribution to photochemical oxidation kg C₂H₄ eq 6.24E-02 1.38E-03 1.16E-05 0* 6.10E-02 1.02E-05

Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Net use of freshwater	m3	5.30E-01	8.48E-02	0*	0*	4.45E-01	8.55E-05
Total Primary Energy	MJ	3.60E+03	1.37E+02	5.04E-01	0*	3.46E+03	5.98E-01




Optional indicators		SmartX Controller AS-P - SXWASPXXX10001					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to fossil resources depletion	MJ	1.86E+03	1.02E+02	5.00E-01	0*	1.76E+03	5.03E-01
Contribution to air pollution	m ³	8.14E+03	8.19E+02	1.51E+00	0*	7.32E+03	3.71E+00
Contribution to water pollution	m ³	8.35E+03	1.18E+03	5.86E+00	0*	7.16E+03	7.39E+00
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Use of secondary material	kg	2.95E-02	2.95E-02	0*	0*	0*	0*
Total use of renewable primary energy resources	MJ	2.51E+02	3.42E+00	0*	0*	2.47E+02	0*
Total use of non-renewable primary energy resources	MJ	3.35E+03	1.34E+02	5.03E-01	0*	3.21E+03	5.98E-01
Use of renewable primary energy excluding renewable primary energy used as raw material	MJ	2.51E+02	3.42E+00	0*	0*	2.47E+02	0*
Use of renewable primary energy resources used as raw material	MJ	0.00E+00	0*	0*	0*	0*	0*
Use of non renewable primary energy excluding non renewable primary energy used as raw mtrl	MJ	3.35E+03	1.34E+02	5.03E-01	0*	3.21E+03	5.98E-01
Use of non renewable primary energy resources used as raw material	MJ	0.00E+00	0*	0*	0*	0*	0*
Use of non renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*
Use of renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*
Waste categories	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Hazardous waste disposed	kg	5.14E+00	4.57E+00	0*	6.50E-02	0*	4.97E-01
Non hazardous waste disposed	kg	6.41E+02	2.22E+00	0*	0*	6.38E+02	0*
Radioactive waste disposed	kg	5.22E-01	1.44E-03	0*	0*	5.20E-01	0*
Other environmental information	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Materials for recycling	kg	1.33E-01	1.53E-02	0*	1.69E-03	0*	1.16E-01
Components for reuse	kg	0.00E+00	0*	0*	0*	0*	0*
Materials for energy recovery	kg	3.94E-02	1.45E-04	0*	1.80E-05	0*	3.92E-02
Exported Energy	MJ	0.00E+00	0*	0*	0*	0*	0*

* represents less than 0.01% of the total life cycle of the reference flow

Life cycle assessment performed with EIME version EIME v5.5, database version 2015-04.

The use phase is the life cycle phase which has the greatest impact on the majority of environmental indicators (based on compulsory indicators).

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

Registration N°	SCHN-2015-00003-V01.01-EN	Drafting rules	PCR-ed3-EN-2015 04 02
Verifier accreditation N°	VH08	Information and reference documents	www.pep-ecopassport.org
Date of issue	10-2015	Validity period	5 years
Independent verification of the declaration and data, in compliance with ISO 14025 : 2010			
Internal	External	X	
The PCR review was conducted by a panel of experts chaired by Philippe Osset (SOLINNEN)			
The elements of the present PEP cannot be compared with elements from another program.			
Document in compliance with ISO 14025 : 2010 « Environmental labels and declarations. Type III environmental declarations »			

Schneider Electric Industries SAS

35, rue Joseph Monier
CS 30323
F- 92506 Rueil Malmaison Cedex
RCS Nanterre 954 503 439
Capital social 896 313 776 €

www.schneider-electric.com

Published by Schneider Electric

SCHN-2015-00003-V01.01-EN

© 2015 - Schneider Electric – All rights reserved

10-2015