



# CoreLine surface-mounted

## SM136V 31S\_37S\_43S/840 PSUW20L120NOCELB3

SM136V | CORELINE SURFACE GEN3 - 840 neutral white - Power supply unit

Philips CoreLine surface-mounted light fixtures deliver on the CoreLine promise of innovative, easy-to-use, high-quality luminaires. These high-quality LEDs are designed to replace existing surface-mounted luminaires with T8 or T5 technology. This CoreLine family also features an innovative new choice of multiple lumen outputs in one single luminaire, called MultiLumen. Instant energy savings and a longer lifetime, make this is an environmentally-friendly and cost-saving surface LED light solution. With a quick-connector feature, our SM136V surface-mounted luminaires are quick and easy to install. Also available within the range are Interact Ready luminaires with integrated wireless communications, which are fully compatible with Interact gateways, sensors and software.

### Warnings and Safety

- The product is IPX0 & as such is not protected against water ingress & as such we strongly recommend that The environment in which The luminaire is to be installed is suitably checked
- If the above advice is not taken and the luminaires are subject to water ingress, Philips / Signify cannot guarantee safe failure & product warranty will become void

### Product data

General Information		Product family code	
Light source replaceable	No	SM136V [CORELINE SURFACE GEN3]	
Number of gear units	1 unit	Lighting Technology	LED
Driver included	Yes	Value ladder	Performance
Service tag	No		

## CoreLine surface-mounted

Light Technical	
Luminous Flux	3,100 3,700 4,300 lumen
Saturated Red (R9)	<50
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	126 lm/W
Color rendering index (CRI)	>80
Flickering value (PstLM)	1
Stroboscopic effect value (SVM)	0.4
Beam angle of light source	- degree(s)
Light source color	840 neutral white
Optic type	Wide beam
Luminaire light beam spread	100°
Unified glare rating CEN	25
Operating and Electrical	
Input Voltage	220-240 V
Line Frequency	50 or 60 Hz
Input Frequency	50 or 60 Hz
Initial CLO power consumption	- W
Average CLO power consumption	- W
Power Consumption	34 W
Inrush current	15.3 A
Inrush time	0.29 ms
Power Factor (Fraction)	0.9
Connection	Connection unit 5-pole
Cable	Cable with connector 3-pole
Number of products on MCB of 16 A type B	35
Temperature	
Ambient temperature range	0 to +25 °C
Controls and Dimming	
Dimmable	No
Driver/power unit/transformer	Power supply unit (ON/OFF)
Control interface	-
Constant light output	No
Mechanical and Housing	
Housing Material	Steel
Reflector material	Polycarbonate
Optic material	Polycarbonate
Optical cover/lens material	Polymethyl methacrylate
Fixation material	Steel
Housing Color	White
Optical cover/lens finish	Diamond
Overall length	1,200 mm
Overall width	200 mm
Overall height	68.5 mm
Dimensions (Height x Width x Depth)	69 x 200 x 1200 mm

Approval and Application	
Ingress protection code	IP20/44 [Finger-protected; wire-protected, splash-proof]
Mech. impact protection code	IK03 [0.3 J]
Sustainability rating	-
Protection class IEC	Safety class I
Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	For mounting on normally flammable surfaces
CE mark	Yes
ENEC mark	ENEC mark
Warranty period	5 years
Photobiological risk	Photobiological risk group 0 @200mm to EN62778
EU RoHS compliant	Yes

Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Initial chromaticity	(0.38, 0.38) SDCM ≤3
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)	
Control gear failure rate at median useful life 50000 h	5 %
Lumen maintenance at median useful life* 50000 h	L85
Lumen maintenance at median useful life* 100000 h	L70

Application Conditions	
Performance ambient temperature Tq	25 °C
Maximum dim level	Not applicable
Suitable for random switching	Yes

Product Data	
Full product code	871869997553100
Order product name	SM136V 31S_37S_43S/840 PSUW20L120NOCELB3
Order code	910505101246
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material number (12NC)	910505101246
Full product name	SM136V 31S_37S_43S/840 PSUW20L120NOCELB3
EAN/UPC - Case	8718699975531



## CoreLine surface-mounted

### Dimensional drawing

