

# PRODUCT DATASHEET

## L 36 W/

Basic T8 | Tubular fluorescent lamps 26 mm, with G13 bases



---

## TECHNICAL DATA

### Electrical data

Nominal wattage	36 W
Construction wattage	36.00 W
Nominal voltage	230 V
Nominal current	0.43 A
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body

### Photometrical data

Luminous flux	2950 lm
Luminous efficacy	81 lm/W
Light color	530
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body

### Dimensions & Weight

Overall length	1200.00 mm
Length with base excl. base pins/connection	1200 mm
Tube diameter	26 mm
Product weight	147.00 g

### Lifespan

Service life	5000 h
--------------	--------

### Additional product data

Base (standard designation)	G13
Mercury content	8.0 mg

### Country-specific categorizations

Order reference	L 36W/530
-----------------	-----------

### Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G13
Length	1200.00 mm

---

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321652379	Sleeve 1	1,210 mm x 28 mm x 27 mm	167.00 g	0.91 dm <sup>3</sup>
4008321652386	Shipping box 25	1,243 mm x 154 mm x 157 mm	6358.00 g	30.05 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.