


**DG MU 3PH 240 4W+G R (908 348)**


- Prewired complete unit without the need for additional overcurrent protection devices
- High discharge capacity due to heavy-duty zinc oxide varistors ( $I_{max}$  50 kA 8x20µs)
- Short circuit current rating (SCCR) 200 kA
- ANSI/UL 1449 – 4<sup>th</sup> Ed. Open-Type 1 SPD



Figure without obligation



Basic circuit diagram DG MU 3PH 240 4W+G R



Dimension drawing DG MU 3PH 240 4W+G R

DIN rail mount, pluggable surge arrester consisting of a base part and plug-in protection modules for application in 3 Phase High-leg Delta Systems; has floating Form C (SPDT) remote status contacts

Type	DG MU 3PH 240 4W+G R
Part No.	908 348
SPD classification acc. to ANSI/UL 1449 4 <sup>th</sup> Ed.	Open-Type 1 SPD
SPD classification acc. to CSA - C22.2 No. 269.1-14	Type 4-1 Component Assembly
Nominal System Voltage [L-N] / [H-N] / [L-G] / [H-G] / [L-L] / [L-H] / [N-G] ( $U_n$ )	120 V a.c. / 208 V a.c. / 120 V a.c. / 208 V a.c. / 240 V a.c. / 240 V a.c. / 0 V a.c.
Nominal Power System Frequency	50 / 60 Hz
Max. continuous operating voltage AC [L-N] / [H-N] / [L-G] / [H-G] / [L-L] / [L-H] / [N-G]	230 V a.c. / 275 V a.c. / 410 V a.c. / 455 V a.c. / 460 V a.c. / 505 V a.c. / 180V a.c.
Nominal discharge current (8x 20 µs) ( $I_n$ )	20 kA
Max. discharge current (8/20) ( $I_{max}$ )	50 kA
Voltage protection rating [L-N] / [H-N] / [L-G] / [H-G] / [L-L] / [L-H] / [N-G] (VPR)	700 V <sub>pk</sub> / 800 V <sub>pk</sub> / 1200 V <sub>pk</sub> / 1500 V <sub>pk</sub> / 1500 V <sub>pk</sub> / 1500 V <sub>pk</sub> / 600 V <sub>pk</sub>
Max. mains-side overcurrent protection	Not needed
Short circuit current rating (SCCR)	200 kA
System type	3 Phase High Leg Delta
Operating Temperature Range ( $T_u$ )	-40°C...+85°C
Operating state / fault indication	Green = Good ; Red = Replace Module
Cross-sectional area (min.)	14 AWG / 2.5 mm <sup>2</sup>
Cross-sectional area (max.)	4 AWG / 25 mm <sup>2</sup>
Terminal Torque Ratings	35-45 Lbs-in
Mounting	35 mm DIN rails acc. to EN 60715
Enclosure material	thermoplastic, red, UL 94 V-0
Degree of protection	IP 20
Capacity	4 module(s), DIN 43880
Approvals	UL, CSA
Remote status contact	Floating (dry), Form C (SPDT)
Remote Status NEC Circuits	NEC Class 2 circuits only
Remote Status Wire Sizes	AWG 16-22 / 1.5 mm <sup>2</sup> - 0.34mm <sup>2</sup>
Remote Status Terminal Torque Ratings	3 Lbs-in
Weight	406 g
Customs tariff number	85363030
GTIN	4013364148796
PU	1 Stk

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.