


FLAT POLYMERO

311947.002.1.76 | Ceiling and wall luminaires



Ceiling and wall luminaires
4051859166511
D 460, H 120

Ceiling mounting, Wall (surface)
white




Decorative round surface-mounted luminaire. Base: metal, powder-coated. Diffuser made of non-yellowing plastic (PMMA), opal. Diffuser fastening: patented push system. Suitable for Ceiling mounting, Wall (surface).

Product specifications

Diameter D	460 mm
Height H	120 mm
Weight	2.69 kg
Light source	LED
Colour temperature	3000 K
Rated luminous flux	1950 lm
System power	19 W
System efficiency	103 lm/W
Glare evaluation UGR (4H 8H)	18,9
Beam angle	down 116° up 180°
Rated life	50000 h (L80/B10)
Colour rendering index (CRI)	83
Colour tolerance	3
Photobiological safety according to EN 62471	Risk group 1
Driver	Converter, dimmable
Control	DALI
Voltage	220 - 240 V / 50 - 60 Hz
Luminaires on B10A fuse	87
Luminaires on B16A fuse	139
Luminaires on C10A fuse	87
Luminaires on C16A fuse	139
Inrush current / Inrush current duration	0.1 A / 10000 µs
CIE Flux Code / CEN Flux Code	43 73 91 90 100
Type of protection	IP 40
Protection class	I
Filament test	650°C - 30 seconds
Impact resistance	IK03
Ambient temperature	25 °C
Conformity mark	CE, EAC

Spareparts



08-311165.012
Replacement diffuser