

# SLI033034CCT\_PW

SLI033034CCT\_PW



|                           |                      |                    |                         |
|---------------------------|----------------------|--------------------|-------------------------|
| Power                     | <b>8 W</b>           | Voltage            | <b>230 V</b>            |
| Luminous flux*            | <b>800 lm (360°)</b> | Colour temperature | <b>2700/4000/6000 K</b> |
| Colour of light           | <b>CCT</b>           | Beam angle         | <b>25 °</b>             |
| Degree of protection (IP) | <b>IP20</b>          |                    |                         |

## Technical data


---

|                              |  |
|------------------------------|--|
| Code                         | SLI033034CCT_PW                                    |
| Power                        | 8 W  |
| Nominal current              | 68 mA  |
| Voltage                      | 230 V  |
| Energy consumption           | 8 kWh/1000h  |
| Frequency                    | 50HZ Hz  |
| Protection class             | I  |
| Power factor                 | 0,5  |
| Useful luminous flux*        | 800 lm (360°)                                      |
| Luminous flux**              | 600 lm (360°)                                      |
| Lamp efficacy                | 100 lm/W   |
| Luminous intensity           | 3000 cd  |
| Colour temperature           | 2700/4000/6000 K                                   |
| Colour of light              | CCT  |
| Beam angle                   | 25 °   |
| RA                           | 80   |
| Light source included        | Yes  |
| Uniformity of color SDCM max | 5  |
| Dimmable                     | No   |
| Working temperature range    | -20/+40 °  |
| Lifespan                     | 17000 h  |
| Housing material             | Aluminum, PLASTIC                                  |
| Degree of protection (IP)    | IP20   |
| Colour                       | Black  |
| Dimension (AxBxC)            | 54x109x160 mm                                      |
| For use                      | Inside/Outside                                     |
| Assembly method              | on track   |
| Application                  | Inside   |
| Made in                      | PRC  |
| Other                        | Light color change function<br>2700K/4000K/6000K , |

## Related documents

---



 User manual