

---

PRODUCT-DETAILS

# OS63GD04FP

## OS63GD04FP SWITCH FUSE



---

### General Information

Extended Product Type	OS63GD04FP
Product ID	1SCA115228R1001
EAN	6417019476537
Catalog Description	OS63GD04FP SWITCH FUSE
Long Description	Switch Fuses,Front Operated,4-pole,04 (Left Side),DIN,000,Handle and shaft included,Switched - Fusible Pole

---

### Circular Value

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SCC011021D0201
RoHS Information	1SCC011020D0201

---

### Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

---

## Popular Downloads

---

Data Sheet, Technical Information	1SCC311013C0201
Instructions and Manuals	1SCC311036M0212

---

## Dimensions

---

Product Net Width	136 mm
Product Net Height	125 mm
Product Net Depth / Length	121 mm
Product Net Weight	1.39 kg 3.06 lb

---

## Technical

---

Rated Operational Current AC-21A ( $I_e$ )	(500 V) 63 A (690 V) 63 A
Rated Operational Current AC-22A ( $I_e$ )	(500 V) 63 A (690 V) 63 A
Rated Operational Current AC-23A ( $I_e$ )	(500 V) 63 A (690 V) 63 A
Rated Operational Power AC-23A ( $P_e$ )	(220 ... 240 V) 18.5 kW (400 V) 30 kW (415 V) 30 kW (500 V) 37 kW (690 V) 55 kW
Conventional Free-air Thermal Current ( $I_{th}$ )	$\Theta = 40\text{ °C}$ 63 A
Conventional Thermal Current ( $I_{the}$ )	Fully Enclosed 63 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	12 kV
Rated Insulation Voltage ( $U_i$ )	1000 V
Rated Operational Voltage	Main Circuit 690 V AC
Rated Short-time Withstand Current Low Voltage ( $I_{cw}$ )	for 1 s 2.5 kiloampere rms
Rated Conditional Short-Circuit Current ( $I_{nc}$ )	(690 V) 80 kA
Power Loss	at Rated Operating Conditions per Pole 7.5 W
Pollution Degree	3
Handle Type	Pistol handle and shaft included
Fourth Pole Type	Switched - Fusible Pole
Switches Operating Mechanism	04 (Left Side)
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out

Fuse Size	NH000
Fuse System	DIN
Operating Mode	Front Operated
Standards	IEC 60947-3
Mounting Type	Base mounting
Number of Poles	4
Cable Cross-Section	2.5 ... 25 mm <sup>2</sup>
Terminal Type	Screw Terminals
Tightening Torque	3 N·m 4 N·m
Rated Current (I <sub>n</sub> )	Main Circuit 63 A

### Technical UL/CSA

Tightening Torque	3 N·m 4 N·m
-------------------	----------------

### Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
-------------	--

### Certificates and Declarations

CCC Certificate	CCC OS32-63G_2016.pdf
Declaration of Conformity - CE	1SCC311136D2703
DNV GL Certificate	1SCC311125D0203
EAC Certificate	EAC OT_OTDC_OTL_OTP_OTR_OTU_OTE_OETL_OESA_OESC_OTM_OS_OSM_ .pdf
REACH Declaration	1SCC011021D0201

### Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	170 mm 6.7 in
Package Level 1 Depth / Length	190 mm 7.5 in
Package Level 1 Height	145 mm 5.7 in
Package Level 1 Gross Weight	1.5 kg 3.4 lb
Package Level 1 EAN	6417019476537

### Classifications

Object Classification Code	Q
----------------------------	---

ETIM 7	EC001040 - Fuse switch disconnecter
ETIM 8	EC001040 - Fuse switch disconnecter
ETIM 9	EC001040 - Fuse switch disconnecter
eClass	V11.1 : 27371401
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3660337

---

## Categories

---

Low Voltage Products and Systems → Switches → Switch Fuses

