

SLI035056WW_PW_DIM

SLI035056WW_PW_DIM



| | | | |
|---------------------------|-----------------------|--------------------|---------------|
| Power | 40 W | Voltage | 230 V |
| Luminous flux* | 5200 lm (360°) | Colour temperature | 3000 K |
| Colour of light | WW | Beam angle | 120 ° |
| Degree of protection (IP) | IP20 | | |


Technical data

| | |
|------------------------------|--------------------|
| Code | SLI035056WW_PW_DIM |
| Power | 40 W |
| Nominal current | 186 mA |
| Voltage | 230 V |
| Energy consumption | 40 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | II |
| Power supply included | + |
| Power factor | 0.9 |
| Useful luminous flux* | 5200 lm (360°) |
| Luminous flux** | 4500 lm (360°) |
| Lamp efficacy | 130 lm/W |
| Colour temperature | 3000 K |
| Colour of light | WW |
| Beam angle | 120 ° |
| RA | >80 |
| Uniformity of color SDCM max | 5 |
| Dimmable | OPC |
| Working temperature range | -20/+40 ° |
| Lifespan | 50000 h |
| Housing material | Aluminum/Plastic |
| Degree of protection (IP) | IP20 |
| Colour | White |
| Dimension (AxBxC) | 595x595x26 mm |
| Mounting hole | 575x575mm mm |
| For use | Inside |
| Assembly method | Recessed |
| Application | INT |
| Made in | PL |



Related documents



 Declaration of Conformity

