

ALGINE 2w1

SLI037027WW_PW

See
more

Downlight luminaire ALGINE 2w1, with a power of 6 W, high light efficacy 122 lm/W. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Suitable for both surface and recessed mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.


IK06



Power	6 W	Voltage	230 V
Luminous flux*	750 lm (360°)	Colour temperature	3000 K
Colour of light	WW	Beam angle	110 °
IK	06	Degree of protection (IP)	IP20


Technical data

Code	SLI037027WW_PW
Power	6 W
Nominal current	48 mA
Voltage	230 V
Energy consumption	6 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	Yes
Power factor	0,5
Useful luminous flux*	750 lm (360°)
Luminous flux**	550 lm (360°)
Lamp efficacy	122 lm/W
Luminous intensity	220 cd
Colour temperature	3000 K
Colour of light	WW
Beam angle	110 °
RA	>80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 to +40 °
Lifespan	17000 h
Housing material	PLASTIC
IK	06
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	115x35 mm
Mounting hole	95 mm
For use	Inside
Assembly method	On the ceiling, Recessed
Application	Inside
Made in	PRC




Related documents



 User manual



 Declaration of Conformity



 Photometric file



 3D model

