




1 electromechanical relay 24Vdc
4PDT 6A, screw, pluggable



| | |
|--|--|
| Series | CM |
| Code | XCM4C024 |
| Type | CM4C024 |
| HS code | 85364190 |
| INPUT TECHNICAL DATA | |
| Input rated voltage | 24 Vdc $\pm 10\%$ |
| Pull in / drop out voltage type | 18 V / 2.4 V |
| Current consumption | 40 mA $\pm 10\%$ |
| Turn ON / OFF time | 20 ms / 20 ms |
| Protection circuit | Free-wheel diode |
| Connection terminal | 2.5 mm ² screw |
| Input channels | 1 pluggable |
| OUTPUT TECHNICAL DATA | |
| Contact type | 4PDT, 4 form C, AgNi |
| Nominal current | 6 A (240 Vac) |
| Continuous current | 12 A |
| Min applicable load | 10 mA / 12 V |
| Connection type | |
| GENERAL TECHNICAL DATA | |
| Operating temperature range | -20...+60°C |
| Input / output isolation | 2.5 kVac / 60 s |
| Protection degree | IP 20 |
| Oversoltage category / pollution degree | II / 2 |
| Status indication | LED "Input" |
| Housing material | UL94V-0 plastic material |
| Dimensions (LxHxD) | 27x75x68 mm |
| Approximate weight | 54 g |
| Mounting information | on a rail, side by side |
| ACCESSORIES | |
| Mounting rail (IEC60715/TH35-7.5) | PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB |
| Marking tag | already mounted |
| Spare part relay | 8904069 |
| Plugin jumper | CMB27B (6 poles) |
| APPROVALS AND MARKINGS | CE |



* Pluggable relay* DC input voltage* 4PDT contact* Compact dimensions* Available plug-in jumper for potential distribution
1 Manufacturer and model of the relay is not binding, technical data are to be considered typical

DESCRIZIONE DEL PRODOTTO

CM4C024 1
electromechanical relay 24Vdc 4PDT 6A, screw, pluggable