

PRODUCT-DETAILS

# CMS-200S8

## CMS-200S8 Sensor



### General Information

Extended Product Type	CMS-200S8
Product ID	2CCA880136R0001
EAN	7612271426644
Catalog Description	CMS-200S8 Sensor
Long Description	CMS-200S8 25 mm - Solid-Core Sensor - 40A

### Technical

Rated Operational Voltage	690 V AC 1500 V DC
Frequency (f)	Rated Current 50 Hz atRatedLoad 0.27 W
Accuracy	0.5% FS
Measuring Range	0.1...80 A
Mounting Type	Surface Mounting
Sensor Type	Solid-core (25 mm)
Output	Other

---

### Environmental

---

Ambient Air Temperature	Operation -25 ... 70 °C
RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment
RoHS Information	2CCC413008D0206
Environmental Information	2CCC481001D0202
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

---



---

### Dimensions

---

Product Net Width	26.5 mm
Product Net Height	26.5 mm
Product Net Depth / Length	43 mm
Product Net Weight	28 g

---



---

### Ordering

---

Minimum Order Quantity	1 piece
Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	83 g

---



---

### Certificates and Declarations

---

Declaration of Conformity - CE	2CCC481017D0201
--------------------------------	-----------------

---



---

### Installation

---

Instructions and Manuals	9AKK106930A6241
--------------------------	-----------------

---



---

### Popular Downloads

---

Data Sheet, Technical Information	2CCC481003C0201
-----------------------------------	-----------------

---



---

### Classifications

---

ETIM 8	EC002475 - Current value transformer
ETIM 9	EC002475 - Current value transformer
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	90303900
UNSPSC	41111928
eClass	V11.0 : 27210123

---

---

IDEA Granular Category  
Code (IGCC)

6160 >> Current sensors

Object Classification Code

---

P

---

## Categories

---

Low Voltage Products and Systems → Modular DIN Rail Products → Energy Efficiency Devices → Circuit Monitoring Systems

