



# MASTER UltraEfficient LED candles and lusters

## MAS LEDCandleND2.3-40W E14 830B35 CLG UE

This is the most efficient LED candle from Philips brand. 210lm/W helps to concrete the company statement of sustainability. 50000 hour lifetime helps to extend the replacement cycle to reduce the waste. This is not only the high SPEC product, but also keep the light quality of Philips brand

### Product data

General Information	
Cap-Base	E14 [E14]
CE mark	Yes
EU RoHS compliant	Yes
Nominal lifetime	50,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
Flux measurement reference	Sphere

Light Technical	
Color Code	830 [CCT of 3000K]
Luminous Flux	485 lumen
Color Designation	White (WH)
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	210 lm/W
Color Consistency	<6
Color rendering index (CRI)	80

LLMF At End Of Nominal Lifetime (Nom) 70 %	
--	--

Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	2.3 W
Lamp Current (Nom)	30 mA
Wattage Equivalent	40 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.35
Voltage (Nom)	220-240 V

Temperature	
T-Case Maximum (Nom)	70 °C

# MASTER UltraEfficient LED candles and lusters

## Controls and Dimming

Dimmable No

## Mechanical and Housing

Bulb Finish Clear

Bulb Shape B35 [B 35mm]

## Approval and Application

Energy Consumption kWh/1000 h 3 kWh


EPREL Registration Number 1,370,032

## Product Data

Full product code 871951443595700



Order product name	MAS LEDCandleND2.3-40W E14 830B35 CLG UE
Order code	929003480802
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material number (12NC)	929003480802
Net weight	0.030 kg
Full product name	MAS LEDCandleND2.3-40W E14 830B35 CLG UE
EAN/UPC - Case	8719514435964

## Dimensional drawing



Product	D	C
MAS LEDCandleND2.3-40W E14 830B35 CLG UE	35 mm	125 mm

## Photometric data




Spectral Power Distribution Colour - MAS LEDCandleND2.3-40W E14 830B35 CLG UE



Light Distribution Diagram - MAS LEDCandleND2.3-40W E14 830B35 CLG UE

# MASTER UltraEfficient LED candles and lusters

## Photometric data



## Lifetime



Life Expectancy Diagram - MAS LEDCandleND2.3-40W E14 830B35 CLG UE

Lumen Maintenance Diagram - MAS LEDCandleND2.3-40W E14 830B35 CLG UE

