

CABINET SWITCH

SLI028211_PW



See
more

Furniture luminaire CABINET SWITCH, with a power of 14 W, high light efficacy 120 lm/W. It shines with a cold light colour (6000K), which is suitable for rooms where we need to be most focused and concentrated, such as technical workstations. Designed for surface mounting.




| | | | |
|---------------------------|-----------------------|--------------------|---------------|
| Power | 14 W | Voltage | 230 V |
| Luminous flux* | 1680 lm (360°) | Colour temperature | 6000 K |
| Colour of light | CW | Beam angle | 120 ° |
| Degree of protection (IP) | IP20 | | |

Technical data


| | |
|------------------------------|--|
| Code | SLI028211_PW |
| Power | 14 W |
| Nominal current | 115 mA |
| Voltage | 230 V |
| Energy consumption | 14 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | II |
| Power supply included | + |
| Power factor | 0.6 |
| Useful luminous flux* | 1680 lm (360°) |
| Luminous flux** | 1400 lm (360°) |
| Lamp efficacy | 120 lm/W |
| Colour temperature | 6000 K |
| Colour of light | CW |
| Beam angle | 120 ° |
| RA | >80 |
| Light source included | + |
| Uniformity of color SDCM max | 5 |
| Dimmable | No |
| Working temperature range | -20 +40 ° |
| Lifespan | 17000 h |
| Housing material | Plastic |
| Degree of protection (IP) | IP20 |
| Colour | White |
| Dimension (AxBxC) | 1192x25x36 mm |
| For use | Inside |
| Assembly method | On the ceiling |
| Application | Inside |
| Made in | PRC |
| Other | Maks 7 sztuk w lini/Max 7 pcs per line , |

Related documents



 User manual



 Declaration of Conformity

