


Model	Material	Dimensions (mm)	Weight (g)
T0210	Polyamide UL94V-0	12 x 47 x 56	1.5

Screw terminal block 16mm²,
1-level, earth connection, for TH35 rail

Series	TE
Code	T0210
Type	TE.16/O
HS code	85369010
Colour	Yellow-green
TECHNICAL FEATURES	
Function/Type	Earth terminal blocks
Rated cross-section	16 mm ²
Connecting capacity	
Flexible wire	0.5-16 mm ²
Rigid wire	0.5-25 mm ²
Wire with ferrule - ferrule type	16 mm ² - WP160/22
Electrical characteristics according to IEC EN standard	
Maximum voltage AC/DC	-
Maximum current (rated cross-section)	-
Caliber	B7
Electrical characteristics according to UL Standard	
Maximum voltage AC/DC	600 V
Maximum current (rated cross-section)	-
Section (min-max)	20-3 (AWG)
Tightening torque value (UL)	13.3 lb.in
Electrical characteristics according to ATEX directive and IEC Ex standard	
Maximum voltage AC/DC	-
Maximum current (rated cross-section)	76 A
Operating temperature Min/Max	-40 °C / +110 °C
Rated impulse withstand voltage / pollution degree	8 kV / 3
Insulation stripping length	13 mm
Tightening torque value (nom. / max.)	1.8 / 3 Nm
Width (pitch)	12 mm
Length	47 mm
Height mounted on TH35-7.5/TH35-15/G32	56 / 64 / - mm
Insulation material temperature index (EN 60216-1)	130 °C
Plastic material	Polyamide UL94V-0
ACCESSORIES	
End section	
Grey	-
Green	-
Thickness	-
Cross-connection	
Marking	
Single marking tag	CNU/8/51 (cod. NU0851S) - CNU/10/61 (cod. NU1061S)
Single marking tag for pitch insertion	-
End bracket	
TH35 screw type	BT/3 (cod. BT003)
TH35 snap-fit type	BTO (cod. BT007)
TH35 and G32 snap-fit type	BTU (cod. BT005)
Mounting rail	
IEC 60715/TH35	PR/3/...
IEC 60715/G32	PR/DIN/...
APPROVALS AND MARKINGS	



DESCRIZIONE DEL PRODOTTO

TE.16/O Screw
terminal block 16mm², 1-level, earth connection, for TH35 rail