



CorePro LEDlinear MV

CorePro R7S 118mm 7.2-60W 840

CorePro R7S is a retrofit replacement for traditional double-ended linear R7S lamps. Its ‘light all around’ design delivers light just like a halogen lamp. Within the range you can choose dimmable products which have deep dimming function that enables a cozy ambience when using a dimmable fixture.

Product data

General Information		Starting Time (Nom)	
Cap-Base	R7S [R7s]		0.5 s
Nominal lifetime	15,000 hour(s)	Warm-up time to 60% light	0.5 s
Switching Cycle	8,000	Power Factor (Fraction)	0.5
Lighting Technology	LED	Voltage (Nom)	220-240 V
Flux measurement reference	Sphere		
Light Technical		Temperature	
Color Code	840 [CCT of 4000K]	T-Case Maximum (Nom)	110 °C
Luminous Flux	850 lumen		
Color Designation	Cool White (CW)	Controls and Dimming	
Correlated Color Temperature (Nom)	4000 K	Dimmable	No
Luminous Efficacy (rated) (Nom)	118.00 lm/W	Mechanical and Housing	
Color Consistency	<6	Bulb Finish	Clear
Color rendering index (CRI)	80	Bulb Shape	Linear
LLMF At End Of Nominal Lifetime (Nom)	70 %	Approval and Application	
Operating and Electrical		Suitable For Accent Lighting	No
Line Frequency	50 to 60 Hz	Energy Consumption kWh/1000 h	8 kWh
Input Frequency	50 to 60 Hz	EPREL Registration Number	624,211
Power Consumption	7.2 W	CE mark	Yes
Lamp Current (Nom)	40 mA	EU RoHS compliant	Yes
Wattage Equivalent	60 W		

CorePro LEDlinear MV

Product Data

Full product code	871951430399700
Order product name	CorePro R7S 118mm 7.2-60W 840
Order code	929002495102
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10



Material number (12NC)	929002495102
Full product name	CorePro R7S 118mm 7.2-60W 840
EAN/UPC - Case	8719514304000

Dimensional drawing




Product	D	C
CorePro R7S 118mm 7.2-60W 840	15 mm	118 mm

Photometric data



© 2023 Philips Lighting B.V. Page 1/1

Spectral Power Distribution Colour - CorePro R7S 118mm 7.2-60W 840



Light Distribution Diagram - CorePro R7S 118mm 7.2-60W 840

CorePro LEDlinear MV

Lifetime



Life Expectancy Diagram - CorePro R7S 118mm 7.2-60W 840

Lumen Maintenance Diagram - CorePro R7S 118mm 7.2-60W 840

