

# DURE 3

SLI043009NW\_PW

[See more](#)

Downlight luminaire DURE 3, with a power of 24 W, high light efficacy 121 lm/W. It has a high IP54 rating, making it ideal for use in rooms with high humidity. Lights up with neutral light - the most universal colour (4000K), which is suitable for the rooms we use on a daily basis, ensuring comfort during everyday activities. Designed for recessed mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.

**IP54****IK06**

Power	<b>24 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>2900 lm (360°)</b>	Colour temperature	<b>4000 K</b>
Colour of light	<b>Neutral white</b>	Beam angle	<b>110 °</b>
IK	<b>6</b>	Degree of protection (IP)	<b>IP54</b>


## Technical data

Code	SLI043009NW_PW
Power	24 W
Nominal current	175 mA
Voltage	230 V
Energy consumption	24 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power factor	0.6
Useful luminous flux*	2900 lm (360°)
Luminous flux**	1900 lm (360°)
Lamp efficacy	121 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	110 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	PC+PS
IK	6
Degree of protection (IP)	IP54
Colour	White
Dimension (AxBxC)	220x34 mm
Mounting hole	195 mm
For use	Inside
Assembly method	Recessed
Application	INT
Made in	PRC




## Related documents



 User manual



 Declaration of Conformity



 Photometric file



 3D model

