

# WLD+40037\_SMART

WLD+40037\_SMART

---



---

Power	<b>10 W</b>	Voltage	<b>48 V</b>
Colour temperature	<b>3000/4000/6000 K</b>	Colour of light	<b>CCT</b>
Beam angle	<b>100 °</b>	Degree of protection (IP)	<b>IP20</b>

---

## Technical data


---

Code	WLD+40037_SMART
Power	10 W
Nominal current	210 mA
Voltage	48 V
Energy consumption	10 kWh/1000h
Frequency	DC Hz
Protection class	III
Power factor	1
Useful luminous flux*	940 lm (360°)
Luminous flux**	400 lm (360°)
Lamp efficacy	94 lm/W
Colour temperature	3000/4000/6000 K
Colour of light	CCT
Beam angle	100 °
RA	>90
Light source included	Yes
Uniformity of color SDCM max	5
Working temperature range	-20 to +40 °
Lifespan	50000 h
Housing material	AL+PC
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	304x23x42 mm
For use	Inside
Assembly method	NA SZYNE
Application	Inside
Made in	PRC
Other	CCT/DIM ,

## Related documents

---



 User manual



 Declaration of Conformity

48V

5  
lat  
bez  
płatności  
25% w ratach



20 mm

304 mm

29 mm

45 mm

Montaż oprawy w obrebie szyny na „click” oraz  
możliwość swobodnego jej przesuwania

