

PRODUCT-DETAILS

CA38R

CA38R ComfortLine Compact distribution board, Surface-mounted, 252 SU, Geïsoleerd, IP44, Field Width: 3, Rows: 7, 1250 mm x 800 mm x 160 mm



Algemene informatie

| | |
|---------------|-----------------|
| Type | CA38R |
| Artikelnummer | 2CPX052244R9999 |
| EAN | 4011617522447 |

| | |
|--------------|---|
| Omschrijving | CA38R ComfortLine Compact distribution board, Surface-mounted, 252 SU, Geïsoleerd, IP44, Field Width: 3, Rows: 7, 1250 mm x 800 mm x 160 mm |
|--------------|---|

| | |
|--------------|---|
| Omschrijving | Compact distribution board, partly assembled cabinet, for the internal use, with Door, class of protection II (double insulated), in combination with earthing set (accessory) we can achieve protection class 1, degree of protection IP44, applicable standards: EN 61439-1, EN 61439-3, Rated operational voltage 400V AC 50/60 Hz, rated current 125 A, Powder-coated, in RAL 9016, enclosure out of sheet steel, double door, door out of sheet steel, in RAL 9016, with Standard closure, door opening angle 120 degree, door hinge right and left, cable entry on top via membrane flange mounted, on bottom via flange opening pre-punched, dimensions in mm (H x W x D): 1250 x 800 x 160, Grid unit 8 GU, panel width 3, 7-rows, Space units 252, Row distance in mm: 150, covers out of Plastic, 90 degree press and turn closure, RAL 7035, with N/PE Quick-terminal, cable fastening rail integrated, Assembled with distribution module, device support removable |
|--------------|---|

Technical

| | |
|-----------------------------|---|
| Normen | DIN EN 61439-3 |
| Nominaal bedrijfsvoltage | Maximum 400 V |
| Operationeel voltage | 400 V |
| Toegekende stroom (I_n) | 125 A |
| Vermogensverlies | $\Delta t = 20K$ 93.8 W $\Delta t = 25K$ 123.9 W $\Delta t = 30K$ 146.3 W |

| | |
|------------------------|------------------------------------|
| Aantal rijen | 7 |
| Type sluiting | Turn Handle |
| Configuratietype | Assembled with distribution module |
| Afdekplaattype | Door |
| Behuizingstype | compact distribution boards |
| Montagetype | Surface-mounted |
| Deurtype | Dubbele deur |
| Uitvoering oppervlakte | Powder-coated |
| Materiaal behuizing | Steel |
| Afdekstijl | Closed |
| DIN-plaatseenheden | 252 |
| RAL-nummer | RAL 9016 - Verkeerswit |
| Kleur | Traffic white |
| Terminaltype | Quick-Terminal |

Environmental

| | |
|---------------------------------------|--|
| Beschermingsgraad | IP44 |
| Beschermingsklasse | Geïsoleerd |
| RoHS-status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| RoHS-informatie | 9AKK107680A4771 |
| REACH-verklaring | 2CPC100005X0201 |
| Rapport over conflictmineralen (CMRT) | 9AKK108468A3363 |

Dimensions

| | |
|--------------------------------|-----------|
| Breedte in module-eenheden | 36 |
| Product netto breedte | 800 mm |
| Product netto hoogte | 1250 mm |
| Product netto diepte | 160 mm |
| Product netto gewicht | 34.167 kg |
| Inbouwdiepte (t ₂) | 0 mm |

Ordering

| | |
|----------------------------|-------------|
| Minimale bestelhoeveelheid | 1 stuk |
| Pakketniveau 1 Units | pack 1 stuk |
| Pakketniveau 1 Brutowicht | 35.534 kg |

Certificates and Declarations

| | |
|------------------------------|-----------------|
| Conformiteitsverklaring - CE | 9AKK107680A4771 |
|------------------------------|-----------------|

Installation

| | |
|------------------------------|-----------------|
| Instructies en handleidingen | 2CPC133150M5601 |
|------------------------------|-----------------|

Popular Downloads

| | |
|-------------------------------------|---|
| Gegevensblad, technische informatie | 2CPC000001C0101 2CPC000002C0101 2CPC000377C0101 |
| Building Information Modeling - BIM | 9AKK107680A4427;9AKK107680A4426 |

Classifications

| | |
|--------------------------|---|
| ETIM 8 | EC000214 - Installatiekast met DIN-rail leeg |
| ETIM 9 | EC000214 - Installatiekast met DIN-rail leeg |
| WEEE-categorie | 4. Large Equipment (Any External Dimension More Than 50 cm) |
| AEEA B2C / B2B | Business To Consumer |
| CN8 | 85381000 |
| eClass | V11.0 : 27142409 |
| Object classificatiecode | U |

Accessories

| Identifier | Description | Type | Quantity | Unit Of Measure |
|-----------------|---|--------|----------|-----------------|
| 2CPX052449R9999 | CZL61 ComfortLine Compact CA Enclosure accessories, 15 mm x 200 mm x 300 mm | CZL61 | 1 | piece |
| 2CPX052412R9999 | CZT2 ComfortLine Accessory door, 165 mm x 62 mm x 32 mm | CZT2 | 1 | piece |
| 2CPX052556R9999 | CZ9P16 ComfortLine Interior fitting system, 26 mm x 18.2 mm x 94 mm | CZ9P16 | 1 | piece |
| 2CPX052488R9999 | CZT5 ComfortLine Accessory door, 164 mm x 62 mm x 47 mm | CZT5 | 1 | piece |
| 2CPX052462R9999 | CZ4 ComfortLine Accessory cabinet connection, 20.5 mm x 204 mm x 87 mm | CZ4 | 1 | piece |
| 2CPX052460R9999 | CZ2 ComfortLine Accessory cabinet connection, 30 mm x 50 mm x 13 mm | CZ2 | 1 | piece |
| 2CPX052459R9999 | CZ1P4 ComfortLine Accessory cabinet assembly, 130 mm x 40 mm x 20 mm | CZ1P4 | 1 | piece |
| 2CPX052437R9999 | CZF3 ComfortLine Flange, 22 mm x 223 mm x 106 mm | CZF3 | 1 | piece |
| 2CPX052438R9999 | CZF4 ComfortLine Flange, 22 mm x 223 mm x 106 mm | CZF4 | 1 | piece |
| 2CPX010487R9999 | TZ503 Enclosure accessories, 70 mm x 100 mm x 180 mm | TZ503 | 1 | piece |
| 2CPX010488R9999 | TZ504 Enclosure accessories, 70 mm x 100 mm x 180 mm | TZ504 | 1 | piece |
| 2CPX010489R9999 | TZ505 Enclosure accessories, 70 mm x 100 mm x 180 mm | TZ505 | 1 | piece |
| 2CPX010490R9999 | TZ506 Enclosure accessories, 70 mm x 100 mm x 180 mm | TZ506 | 1 | piece |
| 2CPX010491R9999 | TZ507 Enclosure accessories, 25 mm x 100 mm x 170 mm | TZ507 | 1 | piece |
| 2CPX010492R9999 | TZ508 Enclosure accessories, 25 mm x 100 mm x 170 mm | TZ508 | 1 | piece |
| 2CPX052421R9999 | CZT28H ComfortLine Enclosure accessories, 650.5 mm x 29.5 mm x 5 mm | CZT28H | 1 | piece |

Categorieën

Laagspanningsproducten en -systemen → Verdelers → Onderverdeelborden (System pro E energy) → Compacte verdeelborden - samengestelde modules → ComfortLine Compact CA

