

PRODUCT DATASHEET DULUX S-E 9W-840 2G7 10X1 RU OSRAM

OSRAM DULUX® S/E | Short CFLni, with 4-pin base for ECG operation



Areas of application

- Offices, public buildings
- Shops
- Supermarkets and department stores
- Hotels, restaurants

Product benefits

- Long service life

Product features

- Good color rendering index
- Dimmable (3...100 %)
- Short and compact pin-base lamps with single-turn tubes
- Single-ended four-pin plug-in 2G7 base



TECHNICAL DATA

Electrical data

Nominal wattage	9 W
Construction wattage	8.70 W
Nominal voltage	60 V
Nominal current	0.17 A

Photometrical data

Luminous flux	600 lm
Luminous efficacy	66 lm/W
Color temperature	4000 K
Color rendering index Ra	≥80
Light color	840

Dimensions & Weight

Overall length	151.80 mm
Diameter	12.00 mm
Product weight	21.9 g

Additional product data

Base (standard designation)	2G7
Mercury content	1.6 mg

Capabilities

Dimmable	Yes
----------	-----

Certificates & Standards

Energy efficiency class	G
Energy consumption	9.00 kWh/1000h

Country-specific categorizations

Order reference	DULUX S/E 9W/84

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	2G7
Correlated colour temperature type	SINGLE_VALUE
Length	151.80 mm

Height	12.00 mm
Width	12.00 mm
EPREL ID	546497
Model number	AC34272

EQUIPMENT / ACCESSORIES

- Suitable for operation on electronic control gear

Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854123825	Folding box 1	22 mm x 38 mm x 157 mm	32.00 g	0.13 dm ³
4099854123832	Shipping box 10	126 mm x 86 mm x 173 mm	375.00 g	1.87 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.