


DPG LSA 60 P (906 101)

- Lightning current carrying earthing system for arresters and shield connection
- Integrated mounting frame for LSA blocks with a grid dimension of 30 mm
- Extra space for uninterfered cable routing and surge arresters



Figure without obligation



Dimension drawing DPG LSA 60 P

DPG LSA is a completely premounted enclosure system with LSA mounting frame and allows optimised use of arresters and shield connection systems (constant force spring).

Type	DPG LSA 60 P
Part No.	906 101
Carrying capacity of connection elements D1 Total lightning impulse current (10/350 μ s) (I_{imp})	30 kA
LSA mounting frame for	1x 6 blocks 2/10
Grid dimension of mounting frame	30 mm
Wire guides	2 pc(s).
Cable entries	top / bottom
Cable rail	top / bottom
Lock	yes
For mounting on	walls
Degree of protection	IP 40
Earthing via	earthing block
Dimensions W x H x D	240 x 350 x 130 mm
Enclosure material	sheet steel
Colour	RAL 9016
Weight	4,97 kg
Customs tariff number	85381000
GTIN	4013364106604
PU	1 Stk

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.