

# ALGINE BACKLIGHT

SLI035061NW\_PW



See  
more

LED panel ALGINE BACKLIGHT, with a power of 40 W, high light efficacy 115 lm/W. Lights up with neutral light - the most universal colour (4000K), which is suitable for the rooms we use on a daily basis, ensuring comfort during everyday activities. Suitable for both surface and recessed mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.



Power	<b>40 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>4600 lm (360°)</b>	Colour temperature	<b>4000 K</b>
Colour of light	<b>Neutral white</b>	Beam angle	<b>120 °</b>
Degree of protection (IP)	<b>IP20</b>		

## Technical data


---

Code	SLI035061NW_PW
Power	40 W
Nominal current	182 mA
Voltage	230 V
Energy consumption	40 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	4600 lm (360°)
Luminous flux**	3600 lm (360°)
Lamp efficacy	115 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	120 °
RA	>80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	26000 h
Housing material	Aluminum/STAL/Plastic
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	620x620x28 mm
Mounting hole	590x590 mm
For use	Inside
Assembly method	On the ceiling, Recessed
Application	INT
Made in	PRC

## Related documents

---



 User manual



 Declaration of Conformity