

PRODUCT DATASHEET

LS AY PFM -CP/P2/500

Connectors for LED Strips Performance Class | Connectors for LED Strips Performance Class

Areas of application

- General indoor illumination



Product benefits

- Easy installation of connector, no manual wiring required
- Tool-free installation

TECHNICAL DATA

Electrical data

Nominal voltage	0...36 V
Nominal current	5000 mA

Dimensions & Weight

Length	532 mm
Cable length	500 mm
Width	10.4 mm
Height	4.5 mm
Product weight	9.5 g

Colors & materials

Product color	White
---------------	-------

Temperatures & operating conditions

Ambient temperature range	-15...+45 °C
Temperature range in operation	-15...+45 °C

Certificates & Standards

Type of protection	IP00
--------------------	------

LOGISTICAL DATA

Temperature range at storage	-35...+85 °C
------------------------------	--------------

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075272200	BAG 2	80 mm x 120 mm x 5 mm	20.00 g	0.05 dm ³
4058075272217	Shipping box 100	180 mm x 100 mm x 180 mm	1079.00 g	3.24 dm ³
4058075272224	Shipping box 1,000	520 mm x 380 mm x 210 mm	11557.00 g	41.50 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.