

DK 25 (952 699)


- Allows changing of the wiring level
- For a lightning current suitable installation of arrester combinations



Figure without obligation



Basic circuit diagram DK 25



Dimension drawing DK 25

Feed-through terminal for busbar wiring.

Type	DK 25
Part No.	952 699
Nominal voltage (a.c. / d.c.) (U_N)	500 V
Nominal load current (a.c.) (I_L)	100 A
Test current according to EN 60947-7-1	100 A
Lightning impulse current (10/350 μ s)	100 kA
Rated insulation voltage (U_i)	630 V
Rated impulse withstand voltage (U_{imp})	6 kV
Operating temperature range (T_U)	-40 °C ... +80 °C
Cross-sectional area (min.)	1.5 mm ² solid / flexible
Cross-sectional area (max.)	25 mm ² stranded / 16 mm ² flexible
For mounting on	35 mm DIN rails according to EN 60715
Enclosure material	thermoplastic, red, UL 94 V-0
Degree of protection	IP 20
Capacity	1 module, DIN 43880
Weight	103 g
Customs tariff number	85369095
GTIN	4013364127906
PU	1 Stk

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.