



# CoreLine SlimDownlight

## DN145B LED20S/840 PSU II WH

- LED20S | LED Module, system flux 2000 lm - 840 neutral white - Power supply unit (ON/OFF) - Safety class II

CoreLine SlimDownlight delivers on the CoreLine promise of innovative, easy to use and high-quality indoor LED downlights. CoreLine SlimDownlight is an innovative range of recessed and surface-mounted luminaires that is designed to provide uniform lighting across multiple application areas. With instant energy savings and a longer lifetime, this is an environmentally-friendly and cost-saving solution. Our slim LED downlights fit the same size cut-out, making them simple and easy to install, while the minimal built-in depth of 34mm means they are an ideal space-saving solution, especially for projects with limited space for installation. An Interact ready option with integrated wireless communications is available in this family, which can be used with Interact gateways, sensors and software.

### Product data

General Information	
Lamp family code	LED20S [LED Module, system flux 2000 lm]
Light source replaceable	No
Number of gear units	1 unit
Driver included	Yes
Remarks	*-Per Lighting Europe guidance paper "Evaluating performance of LED based luminaires - January 2018": statistically there is no relevant difference in lumen maintenance between B50 and for example B10. Therefore, the median useful life (B50) value also represents the B10 value.

Service tag	Yes
Lighting Technology	LED
Value ladder	Performance

Light Technical	
Luminous Flux	2,100 lumen
Saturated Red (R9)	<50
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	100 lm/W

# CoreLine SlimDownlight

Color rendering index (CRI)	>80
Number of light sources	1
Beam angle of light source	120 degree(s)
Light source color	840 neutral white
Optic type	Beam angle 90°
Optical cover/lens type	Opal
Luminaire light beam spread	84°
Unified glare rating CEN	28

## Operating and Electrical

Input Voltage	220 to 240 V
Line Frequency	50 or 60 Hz
Input Frequency	50 or 60 Hz
Initial CLO power consumption	- W
Average CLO power consumption	- W
Power Consumption	21 W
Inrush current	28.9 A
Inrush time	0.0016 ms
Power Factor (Fraction)	0.9
Connection	Connection unit 2-pole
Cable	-
Number of products on MCB of 16 A type B	13

## Temperature

Ambient temperature range	0 to +35 °C
---------------------------	-------------

## Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit (ON/OFF)
Control interface	-
Constant light output	No

## Mechanical and Housing

Housing Material	Aluminum die cast
Reflector material	-
Optic material	Polymethyl methacrylate
Optical cover/lens material	Polystyrene
Fixation material	-
Housing Color	White
Optical cover/lens finish	Opal
Overall height	28 mm
Overall diameter	215 mm

## Approval and Application

Ingress protection code	IP20/44 [Finger-protected; wire-protected, splash-proof]
Mech. impact protection code	IK02 [0.2 J standard]
Sustainability rating	-
Protection class IEC	Safety class II
Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	For mounting on normally flammable surfaces
CE mark	Yes
ENEC mark	ENEC mark
Warranty period	5 years
EU RoHS compliant	Yes

## Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	(0.38212,0.38031) SDCM<3
Power consumption tolerance	+/-10%

## Over Time Performance (IEC Compliant)

Driver failure rate at 5000 h	0.0015 %
Control gear failure rate at median useful life 50000 h	5 %
Lumen maintenance at median useful life* 50000 h	L70

## Application Conditions

Performance ambient temperature Tq	25 °C
Maximum dim level	Not applicable
Suitable for random switching	Yes

## Product Data

Full product code	871016333950499
Order product name	DN145B LED20S/840 PSU II WH
Order code	911401806280
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material number (12NC)	911401806280
Full product name	DN145B LED20S/840 PSU II WH
EAN/UPC - Case	8710163339825



# CoreLine SlimDownlight

## Dimensional drawing

