


44423250	DATA SHEET	
Valid from: 31.03.2022	EPIC® MH SCEM AG 1.5sqmm D=4.0	

Description

- For Modules of the EPIC® MH System
- Crimp connection for permanent vibration-proof contact



General characteristics

Contact type	Male / female
Mating cycles	500
Material	Copper alloy
Temperature range	-40° C to +125° C

Artikelnummer <i>Material number</i> Numero de l'article	Artikelbeschreibung <i>Material description</i> Description de l'article	Kontakttyp <i>Contact type</i> Type de contact	Leiterquerschnitt <i>Conductor cross-section</i> Section de conducteur [mm ²]	Oberfläche <i>Surface</i> Superficie	Rillenzahl <i>Number of grooves</i> Nombre de rainures
44423250	EPIC® MH SCEM AG 1.5sqmm D=4.0	Stift	1,5	Ag	2
44423255	EPIC® MH BCEM AG 1.5sqmm D=4.0	Buchse	1,5	Ag	2
44423251	EPIC® MH SCEM AG 2.5sqmm D=4.0	Stift	2,5	Ag	3
44423256	EPIC® MH BCEM AG 2.5sqmm D=4.0	Buchse	2,5	Ag	3
44423252	EPIC® MH SCEM AG 4sqmm D=4.0	Stift	4	Ag	0
44423257	EPIC® MH BCEM AG 4sqmm D=4.0	Buchse	4	Ag	0
44423253	EPIC® MH SCEM AG 6sqmm D=4.0	Stift	6	Ag	1
44423258	EPIC® MH BCEM AG 6sqmm D=4.0	Buchse	6	Ag	1
44423254	EPIC® MH SCEM AG 10sqmm D=4.0	Stift	10	Ag	2
44423259	EPIC® MH BCEM AG 10sqmm D=4.0	Buchse	10	Ag	2

Note

Photographs are not to scale and do not represent detailed images of the respective products.

Creator: JOKR1/PDP Released: IVSE1/PDP	Document: DB44428250EN Version: 00	Page 1 of 1
---	---------------------------------------	-------------