


1 solid

state relay 5-24Vdc/24Vdc 3A screw, not pluggable

Series	
Code	X0332060
Type	O332060
HS code	85364190
INPUT TECHNICAL DATA	
Input rated voltage	5-12-24 Vdc (range 4...30 Vdc)
Pull in / drop out voltage type	3 V / 1 V
Current consumption	35 mA \pm 10%
Turn ON / OFF time	200 μ s / 800 μ s
Frequency	0...500 Hz
Protection circuit	Free-wheel diode
Connection terminal	2.5 mm ² screw
Input channels	1 not pluggable
OUTPUT TECHNICAL DATA	
Contact type	transistor
Output voltage	5...60 Vdc
Nominal current	3 A (24 Vdc) at 20°C
Continuous current	10 A for 10 ms
Leakage current with signal 0	1 mA
Connection type	
Protection circuit device	free-wheel diode
GENERAL TECHNICAL DATA	
Operating temperature range	-20...+70°C (derating -0.5 W/°C over 20°C)
Input / output isolation	2.5 kVac / 60 s
Protection degree	IP 00
Overvoltage category / pollution degree	II / 2
Status indication	LED "Input"
Housing material	UL94V-0 plastic material
Dimensions (LxHxD)	12x77x54 mm
Approximate weight	36 g
Mounting information	vertical on a rail, distance 5 mm from adjacent components
ACCESSORIES	
Mounting rail (IEC60715/TH35-7.5)	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB
Mounting rail (IEC60715/TH35-15)	PR/3/PP, PR/3/PP/ZB, PR/3/PA, PR/3/PA/ZB
Spare part relay	8904407
APPROVALS AND MARKINGS	CE



* Not-pluggable relay* Compact dimension
1 Manufacturer and model of the relay is not binding, technical data are to be considered typical

DESCRIZIONE DEL PRODOTTO

O332060 1 solid state relay 5-24Vdc/24Vdc 3A screw, not pluggable