


Juno Recessed Modular



- Architectural LED recessed modular suitable for education, commercial and healthcare applications
- UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual comfort
- Dual direct / indirect output. Direct from the centre micro-prism centre line coupled with indirect output from the side diffuser sections. Providing a perfect combination for task and ambient lighting from one source
- Black polycarbonate micro reflector low glare design
- Micro-prism diffuser design ensures reduced glare and visual comfort
- OCTO compatible tunable white version available with CCT selection between 2700K-5000K ideal for any Human Centric Lighting requirements
- Powered by Tridonic
- TPa as standard



AJUNLED/TW/OCTO only



OCTO
Option Available


Powered by
CASAMBI



Micro-prism diffuser design ensures reduced glare and visual comfort



Black polycarbonate micro reflector design provides low glare



Indirect illumination provided from the side and direct illumination from the centre

INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	SDCM	BEAM ANGLE	CLASS	IP
220-240V	50-60Hz	-20°C to 40°C	L80 B10 60,000	Ra 80	4	65°	2	Front IP40

CODE	DESCRIPTION	WATTAGE	CCT	LUMENS	LM/W	UGR	TRADE
AJUNLED	600 x 600 - Cool White	34W	4000K	4440lm	131lm	17	£170.00
AJUNLED/TW/OCTO	600 x 600 - Tunable White	37W	2700K-5000K	3860lm (2700K) - 4300lm (6500K)	104lm (2700K) - 116lm (6500K)	17	£410.00

*UGR Value based on (4H - 8H)

CODE (OPTIONS)	DESCRIPTION	TRADE	CODE (OPTIONS)	DESCRIPTION	TRADE
/M3	Emergency	+ £90.00	/OCTO	OCTO Smart Control	+ £195.00
/DM3	DALI Emergency	+ £205.00	/DD	Digital Dimming (DD1/DD3/DD4)	+ £95.00
/SM3	Self-Test Emergency	+ £121.00			

