

# WLD+40000\_CCT

WLD+40000\_CCT



|                    |                         |                           |             |
|--------------------|-------------------------|---------------------------|-------------|
| Power              | <b>5 W</b>              | Voltage                   | <b>48 V</b> |
| Colour temperature | <b>2700/3300/4000 K</b> | Colour of light           | <b>CCT</b>  |
| Beam angle         | <b>165 °</b>            | Degree of protection (IP) | <b>IP20</b> |

## Technical data

---

|                              |                  |
|------------------------------|------------------|
| Code                         | WLD+40000_CCT    |
| Power                        | 5 W              |
| Nominal current              | 100 mA           |
| Voltage                      | 48 V             |
| Energy consumption           | 5 kWh/1000h      |
| Frequency                    | DC Hz            |
| Protection class             | III              |
| Power factor                 | 1                |
| Useful luminous flux*        | 550 lm (360°)    |
| Luminous flux**              | 435 lm (360°)    |
| Lamp efficacy                | 110 lm/W         |
| Colour temperature           | 2700/3300/4000 K |
| Colour of light              | CCT              |
| Beam angle                   | 165 °            |
| RA                           | >90              |
| Light source included        | Yes              |
| Uniformity of color SDCM max | 5                |
| Dimmable                     | No               |
| Working temperature range    | -20 to +40 °     |
| Lifespan                     | 50000 h          |
| Housing material             | AL+PC            |
| Degree of protection (IP)    | IP20             |
| Colour                       | Czarny           |
| Dimension (AxBxC)            | 100x130 mm       |
| For use                      | Inside           |
| Assembly method              | NA SZYŃE         |
| Application                  | Inside           |
| Made in                      | PRC              |
| Other                        | CCT ,            |

## Related documents

---



 User manual