

NOCTIS LUX 3

SLI029051NW_PW



See
more

Floodlight NOCTIS LUX 3, with a power of 50 W. It has a very high degree of protection IP65, providing protection against the ingress of dust and water jets. IK07 class provides impact resistance. It shines with light of neutral - the most universal colour (4000K). Designed for surface mounting.

IP65

IK07



Power	50 W	Voltage	230 V
Luminous flux*	4500 lm (120°)	Colour temperature	4000 K
Colour of light	Neutral white	Beam angle	100 °
IK	07	Degree of protection (IP)	IP65

Technical data

Code	SLI029051NW_PW
Power	50 W
Nominal current	220 mA
Voltage	230 V
Energy consumption	50 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	4500 lm (120°)
Luminous flux**	4500 lm (360°)
Lamp efficacy	90 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	100 °
RA	>70
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, GLASS
IK	07
Degree of protection (IP)	IP65
Colour	Black
Dimension (AxBxC)	180x140x27 mm
For use	Outside
Assembly method	On the ceiling
Application	EXT
Made in	PRC



Related documents



 Declaration of Conformity



 Photometric file

