

ALGINE

SLI035071NW_PW

LED panel ALGINE, with a power of 45 W, high light efficacy 129 lm/W. It is made of high-quality components, supported by a 5-year warranty. Lights up with neutral light - the most universal colour (4000K), which is suitable for the rooms we use on a daily basis, ensuring comfort during everyday activities. Suitable for surface, recessed and suspended mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.




Power	45 W	Voltage	230 V
Luminous flux*	5800 lm (360°)	Colour temperature	4000 K
Colour of light	Neutral white	Beam angle	120 °
UGR	<19	IK	06

Technical data


Code	SLI035071NW_PW
Power	45 W
Nominal current	200 mA
Voltage	230 V
Energy consumption	45 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.95
Useful luminous flux*	5800 lm (360°)
Luminous flux**	4700 lm (360°)
Lamp efficacy	129 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	120 °
UGR	<19
RA	80
Uniformity of color SDCM max	5
Dimmable	DALI
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum, PLASTIC
IK	06
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	595x595x10 mm
For use	Inside
Assembly method	Recessed, On the ceiling, Suspended
Application	INT
Made in	PRC
Other	L90B50 50000h, MTBF 80000h ,

Related documents



 User manual



 Declaration of Conformity