

PRODUCT-DETAILS

PS3/45H2

PS3/45H2 Busbar



General Information

Extended Product Type	PS3/45H2
Product ID	2CDL230001R1045
EAN	4016779653701
Catalog Description	PS3/45H2 Busbar
Long Description	Busbar PS 3/45 H2

Technical

Standards	IEC/EN 60947-1
Suitable For	S200 F200 DDA200
Suitable for Product Class	3-pole devices + 2 auxiliary contacts
Rated Operational Voltage	690 V AC/DC Maximum 690 V
Rated Short-time Withstand Current Low Voltage (I_{cw})	25 kA
Rated Uninterrupted Current (I_U)	63 A
Rated Frequency (f)	50 / 60 Hz DC
Pitch	17.5
Number of Poles	45
Number of Phases	3
Number of Mountable	15

Devices

	45
Overvoltage Category	III
Accessory Type	Busbar
Connection Type	Pin
Housing Material	Light grey, RAL 7035
Options Provided	H2
Mounting Position	any
RAL Number	RAL 7035 - Light Grey
Color	grey
Rated Cross-Section	10 mm ²

Environmental

Pollution Degree	2
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Information	9AKK108468A1264
Environmental Information	DIN EN 60068

Dimensions

Product Net Weight	0.001 kg
--------------------	----------

Ordering

Minimum Order Quantity	1 piece
------------------------	---------

Certificates and Declarations

Declaration of Conformity - CE	9AKK108468A1264
-----------------------------------	-----------------

Installation

Instructions and Manuals	2CSC400002D0208
--------------------------	-----------------

Popular Downloads

Data Sheet, Technical Information	9AKK106930A8017
--------------------------------------	-----------------

Classifications

ETIM 8	EC000215 - Phase busbar
ETIM 9	EC000215 - Phase busbar
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	8536 90 10
UNSPSC	39121117
eClass	V11.0 : 27371306
IDEA Granular Category Code (IGCC)	4378 >> Phase busbar
Object Classification Code	W

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Miniature Circuit Breakers MCBs → Miniature Circuit Breakers MCBs Accessories

