


PRODUCT-DETAILS

## S204P-C40

# S204P-C40 Miniature Circuit Breaker - 4P - C - 40 A



### Algemene informatie

Type	S204P-C40
Artikelnummer	2CDS284001R0404
EAN	4016779590822
Omschrijving	S204P-C40 Miniature Circuit Breaker - 4P - C - 40 A

Omschrijving

System pro M compact S200P miniature circuit breakers are current limiting. They have two different tripping mechanisms, the delayed thermal tripping mechanism for overload protection and the electromechanic tripping mechanism for short circuit protection. They are available in different characteristics (B,C,D,K,Z), configurations (1P,1P+N,2P,3P,3P+N,4P), breaking capacities (up to 25 kA at 230/400 V AC) and rated currents (up to 63A). All MCBs of the product range S200P comply with IEC/EN 60898-1, IEC/EN 609 47-2, UL1077 and CSA 22.2 No. 235, allowing the use for residential, commercial and industrial applications. Bottom-fitting auxiliary contact can be mounted on S200P to save 50% space.

### Technical

Normen	CSA 22.2 No. 235 IEC/EN 60898-1 IEC/EN 60947-2 UL 1077
Uitschakelkenmerk	C
Nominaal bedrijfsvoltage	acc. to IEC 60898-1 400 V AC acc. to IEC 60947-2 400 V AC
Operationeel voltage	Maximum (inclusief tolerantie) 440 V AC Minimum 12 V AC Minimum 12 V DC

Nominaal isolatievoltage (U <sub>i</sub> )	acc. to IEC/EN 60664-1 440 V
Nominale impuls grensvoltage (U <sub>imp</sub> )	4 kV at 2000 m 5 kV at Sea Level 6.2 kV
Diëlektrische testspanning	50/60 Hz, 1 min: 2 kV
Ingangsspanningstype	AC
Toegekende stroom (I <sub>n</sub> )	40 A
Nominaal kortsluitvermogen	(AC) 15 kA (230 V AC) 12.5 kA (400 V AC) 15 kA
Nominaal ultiem kortsluitvermogen (I <sub>cu</sub> )	(230 V AC) 25 kA (400 V AC) 15 kA
Nominale voorwaardelijke kortsluitstroom (I <sub>nc</sub> )	(230 V) 25 kA (400 V) 25 kA
Nominaal vermogen kortsluitvermogen (I <sub>cs</sub> )	(400 V AC) 11.3 kA
Toegekende frequentie (f)	50 / 60 Hz
Vermogensverlies	25.6 W at Rated Operating Conditions per Pole 6.4 W
Aansluiting voeding	Arbitrary
Statusindicator	Red ON / Green OFF
Energiebeperkende klasse	3
Elektrisch uithoudingsvermogen	10000 AC cycle
Mechanisch uithoudingsvermogen	20000 cycle
Aantal polen	4
Aantal beveiligde polen	4
Overspanningscategorie	III
Aanhaalmoment	2.8 N·m
Type schroefklem	Failsafe Bi-directional Cylinder-lift Terminal
Aansturingsmarkering	I / O
Aansturingsmateriaal	Insulation Group II, Black, Sealable
Materiaal behuizing	Insulation Group II, RAL 7035
Montage op DIN-rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Plaats van inbouw	any
Aanbevolen schroevendraaier	Pozidriv 2
Accessoires beschikbaar	Yes
Verbindingscapaciteit	Busbar 10 / 10 mm <sup>2</sup> Flexible with Ferrule 0.75 ... 16 mm <sup>2</sup> Flexible 0.75 ... 16 mm <sup>2</sup> Rigid 0.75 ... 25 mm <sup>2</sup> Stranded 0.75 ... 25 mm <sup>2</sup>
Installatiegrootte	acc. to DIN 43880 1
Terminaltype	Schroef

## Environmental

Omgevingsluchttemperatuur	Werking -25 ... +55 °C Opslag -40 ... +70 °C
Referentie omgevingsluchttemperatuur	30 °C
Beschermingsgraad	IP20

	Enclosure with Cover IP40
Verontreinigingsgraad	3
Milieu-omstandigheden	28 cycles with 55 °C / 90-96 % and 25 °C / 95-100 %
Weerstand tegen trillingen volgens IEC 60068-2-6	5g, 20 cycles at 5 ... 150 ... 5 Hz with load 0.8 In
Schokweerstand volgens IEC 60068-2-27	25g 2 shocks 13 ms
RoHS-status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS-informatie	2CDK403003D0404
REACH-verklaring	9AKK107492A1906
Milieu-informatie	9AKK107680A6947
SCIP	b0ff61fd-fab1-4a8b-9575-6a2e28f174ec Germany (DE)
Rapport over conflictmineralen (CMRT)	9AKK108468A3363

## Technical UL/CSA

Maximale bedrijfsspanning UL/CSA	480Y/277 V AC
Onderbrekende classificatie volgens UL1077	(480Y / 277 V AC) 6 kA
Verbindingscapaciteit UL/CSA	Busbar 18-8 AWG Conductor 18-4 AWG
Aanhaalmoment UL/CSA	25 in-lb

## Dimensions

Breedte in module-eenheden	4
Product netto breedte	70 mm
Product netto hoogte	88 mm
Product netto diepte	69 mm
Product netto gewicht	0.56 kg
Pool netto gewicht	0.14 kg
Inbouwdiepte (t <sub>2</sub> )	69 mm

## Ordering

Minimale bestelhoeveelheid	1 stuk
Pakketniveau 1 Units	karton 1 stuk
Pakketniveau 1 Bruto gewicht	0.57 kg
E-Number (Sweden)	2102165
Vervangen product-ID (NIEUW)	2CDS384001R0404

## Certificates and Declarations

Certificatieagentschap	CSA IEC EN
------------------------	------------------

UL

Conformiteitsverklaring - CE	2CDK403003D0404
---------------------------------	-----------------

## Installation

Instructies en handleidingen	2CDS207104P0002
---------------------------------	-----------------

## Popular Downloads

Gegevensblad, technische informatie	9AKK106930A8017
EPLAN grafische macro	9AKK106713A8206
EPLAN-macro	9AKK106713A8205

## Classifications

ETIM 8	EC000042 - Installatieautomaat
ETIM 9	EC000042 - Installatieautomaat
EPLAN-functiedefinitie	Circuit breaker / Quadruple circuit-breaker / Quadruple circuit-breaker 1_2_3_4_5_6_7_8
WEEE-categorie	5. Small Equipment (No External Dimension More Than 50 cm)
AEEA B2C / B2B	Business To Business
CN8	8536 20 10
UNSPSC	39121603
eClass	V11.0 : 27141901
IGCC (IDEA granulaire categoriecodel)	4897 >> Miniature circuit breakers
Object classificatiecode	F

## Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
2CDS200922R0001	S2C-S/H6R Signal / Auxiliary Contact	S2C-S/H6R	1	piece
2CDS200912R0001	S2C-H6R Auxiliary Contact	S2C-H6R	1	piece
2CDS200936R0001	S2C-H11L Auxiliary Contact	S2C-H11L	1	piece
2CDS200936R0002	S2C-H20L Auxiliary Contact	S2C-H20L	1	piece
2CDS200936R0003	S2C-H02L Auxiliary Contact	S2C-H02L	1	piece
2CDS200946R0001	S2C-H6-11R Auxiliary Contact	S2C-H6-11R	1	piece
2CDS200946R0002	S2C-H6-20R Auxiliary Contact	S2C-H6-20R	1	piece
2CDS200946R0003	S2C-H6-02R Auxiliary Contact	S2C-H6-02R	1	piece
2CDS200909R0001	S2C-A1 Shunt Trip	S2C-A1	1	piece
2CDS200909R0002	S2C-A2 Shunt Trip	S2C-A2	1	piece
2CSS200911R0001	S2C-UA 12 DC Undervoltage release	S2C-UA 12 DC	1	piece
2CSS200911R0002	S2C-UA 24 AC Undervoltage release	S2C-UA 24 AC	1	piece
2CSS200911R0003	S2C-UA 48 AC Undervoltage release	S2C-UA 48 AC	1	piece
2CSS200911R0004	S2C-UA 110 AC Undervoltage release	S2C-UA 110 AC	1	piece
2CSS200911R0005	S2C-UA 230 AC Undervoltage release	S2C-UA 230 AC	1	piece
2CSS200911R0006	S2C-UA 400 AC Undervoltage release	S2C-UA 400 AC	1	piece
2CSS200911R0007	S2C-UA 24 DC Undervoltage release	S2C-UA 24 DC	1	piece
2CSS200911R0008	S2C-UA 48 DC Undervoltage release	S2C-UA 48 DC	1	piece
2CSS200911R0009	S2C-UA 110 DC Undervoltage release	S2C-UA 110 DC	1	piece
2CSS200911R0010	S2C-UA 230 DC Undervoltage release	S2C-UA 230 DC	1	piece
2CSS201997R0013	S2C-CM1 Motor operating device	S2C-CM1	1	piece
2CSS203997R0013	S2C-CM2/3 Motor operating device	S2C-CM2/3	1	piece
2CSS204997R0013	S2C-CM4 Motor operating device	S2C-CM4	1	piece
GHS2001901R0003	S2C-DH Mechanical Accessories	S2C-DH	1	piece
2CSS200998R0001	S2C-BP Mechanical tripping device	S2C-BP	1	piece
2CSS200999R0001	S2C-EST Plug-in base	S2C-EST	1	piece
2CDS200918R0001	S2C-NT Hand Operated Neutral	S2C-NT	1	piece
2CCA880100R0001	CMS-100PS Sensor	CMS-100PS	1	piece
2CCA880101R0001	CMS-101PS Sensor	CMS-101PS	1	piece
2CCA880102R0001	CMS-102PS Sensor	CMS-102PS	1	piece

## Categorieën

Laagspanningsproducten en -systemen → Modulaire DIN rail producten → Miniature Circuit Breakers MCBs → Installatieautomaten MCB's

