

# PLATEO 3 1-10V

SLI044024NW\_PW

See  
more

High bay luminaire PLATEO 3 1-10V, with a power of 100 W, high light efficacy 155 lm/W. It is made of high-quality components, supported by a 5-year warranty. It has a very high degree of protection IP65, providing protection against the ingress of dust and water jets. IK09 class provides impact resistance. It shines with light of neutral - the most universal colour (4000K). Narrow beam angle 90° gives directional light so that selected surfaces can be better exposed. Designed for suspended mounting.



Power	<b>100 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>15500 lm (360°)</b>	Colour temperature	<b>4000 K</b>
Colour of light	<b>Neutral white</b>	Beam angle	<b>90 °</b>
IK	<b>09</b>	Degree of protection (IP)	<b>IP65</b>

## Technical data

Code	SLI044024NW_PW
Power	100 W
Nominal current	450 mA
Voltage	230 V
Energy consumption	100 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power factor	0.95
Useful luminous flux*	15500 lm (360°)
Luminous flux**	15000 lm (360°)
Lamp efficacy	155 lm/W
Luminous intensity	7000 cd
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	90 °
RA	80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	1-10V
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum, PC
IK	09
Degree of protection (IP)	IP65
Colour	Black
Dimension (AxBxC)	250x120 mm
For use	Inside/Outside
Assembly method	Suspended
Application	INT/EXT
Made in	PRC



## Related documents

[User manual](#)[Declaration of Conformity](#)[Photometric file](#)

